


Date	Fixture	Project	Quantity
------	---------	---------	----------

Zip Cloud

Suspended

Features

- Architectural luminaire
- Sleek circular shape
- Pendant mounting
- 4 size options
- Multiple finishes
- Designed and Manufactured in North America
- 5 Year Warranty



Specifications

Construction

Aluminum extruded body
Dry and damp rated for indoor applications

Dimensions

Diameter: 18", 24", 36", 44"
Height: 4"

LED

Samsung LM281B Plus Pro, 3-Step MacAdam Binning
120 Lm/W
L70>200,000

Watts

Zip Cloud 18: 30W, 40W, 60W, 70W
Zip Cloud 24: 20W, 30W, 40W
Zip Cloud 36: 40W, 80W, 120W, 160W
Zip Cloud 44: 80W, 120W, 160W

Color Temperature

2700K - 5000K

CRI

80 or 90

Voltage

120/277V or 347V

Driver

0-10V Dimming down to 1%
No Dimming

Lens

Frosted Flat

Mounting

Aircraft Cable (10' std)

Wiring

Black and White 3 Conductor Wire (No Dimming)
Black and White 5 Conductor Wire

Finishes

Black - RAL 9004, Grey - RAL 7046, White - RAL 9003
Custom RAL finishes available

Certifications

cULus



Ordering Guide

Sample Configuration: ZIP CLOUD - 18 - 70 - 80 - 4K - U - FR - DIRECT - WH - AC - DIMOFF - BFC 5 WIRE - CL - 6 - WH

ZIP CLOUD						FR	DIRECT		AC
Model	Size	Watts	CRI	Color Temp	Voltage	Lens	Distribution	Finish	Mounting
Driver	Wiring	Wire Color	Wire Length	Canopy Finish					

Model	Size	Watts	CRI	Color Temp	Voltage	Lens	Distribution
ZIP CLOUD	18 24 36 44	18: 20, 40, 60, 70 24: 20, 40, 60, 80 36: 40, 80, 120, 160 44: 80, 120, 160	80 90	3K - 3000K 35K - 3500K 4K - 4000K 5K - 5000K	U - 120/277V H - 347V	FR - Frosted Flat	DIRECT

Finish	Mounting	Driver	Wiring
WH - White BLK - Black GRY - Grey CU - Custom* Note: For custom finishes please specify RAL number	AC - Aircraft Cable (10' std)	DIMOFF - 0-10V Dimming down to 1% ND - No Dimming	BFC 3 WIRE - Black 3 Conductor Wire (no dimming) WFC 3 WIRE - White 3 Conductor Wire (no dimming) BFC 5 WIRE - Black 5 Conductor Wire WFC 5 WIRE - White 5 Conductor Wire

Wire Color	Wire Length	Canopy Finish	
CL - Clear Optional B - Black W - White	Length _____ 6' Standard	WH - White BLK - Black CU - Custom* Note: Please contact factory for custom finishes	

Dimensions




Ø: 18", 24", 36", 44"
H: 4.0"

Output Performance

Model	Watts	Lm/W	Delivered Lumens
Zip Cloud 18	20	120	2,400
	40		4,800
	60		7,200
	70		8,400
Zip Cloud 24	20	120	2,400
	40		4,800
	60		7,200
	80		9,600
Zip Cloud 36	40	120	4,800
	80		9,600
	120		14,400
	160		19,200
Zip Cloud 44	80	120	9,600
	120		14,400
	160		19,200


Mounting Options



Ø 4.5"
Power Feed



Ø 2"
Non Power Feed



Aircraft Cable Canopy / Drywall Anchor

Finish Options

Standard Finishes



Signal White
RAL 9003

Telegrey 2
RAL 7046

Signal Black
RAL 9004

Custom Finishes



Traffic White
RAL 9016

Papyrus White
RAL 9018

Graphic Grey
RAL 7024

Jet Black
RAL 9005

Graphic Black
RAL 9011

Azure Blue
RAL 5009

Gentian Blue
RAL 5010

Sky Blue
RAL 5015



Pastel Orange
RAL 2003

Pure Orange
RAL 2004

Lemon Yellow
RAL 1012

Zinc Yellow
RAL 1018

Coral Red
RAL 3016

Rose
RAL 3017

Traffic Red
RAL 3020

Salmon Pink
RAL 3022



Olive Green
RAL 6003

Grass Green
RAL 6010

Claret Violet
RAL 4004

Traffic Purple
RAL 4006

Pearl Blackberry
RAL 4012

Beige
RAL 1001

Nut Brown
RAL 8011

Sepia Brown
RAL 8014

Please contact factory for additional and custom Finishes

Canopy Finishes



Signal White
RAL 9003

Telegrey 2
RAL 7046

Signal Black
RAL 9004