


Zip Cloud Square Pendant

Features

- Architectural luminaire
- · Low profile square design
- Direct and Direct/Indirect distribution
- Pendant mounting
- 2 size options
- Multiple finishes
- Dry and damp for indoor applications
- Designed and Manufactured in North America
- 5 Year Warranty



Specifications

Construction

Aluminum extruded body Powder coated finish

Dimensions

Zip Cloud Square 18: 18"w x 18"l x 4"h Zip Cloud Square 25: 25"w x 25"l x 4"h

LED

Samsung LM281B Plus Pro, 3-Step MacAdam Binning L70>200,000

Watts: Direct Zip Cloud Square 18: 20W, 40W Zip Cloud Square 25: 20W, 40W, 60W, 80W

Watts: Indirect Zip Cloud Square 25: 40W

Color Temperature 2700K - 5000K

CRI

80 or 90

Voltage 120/277V or 347V

Driver

0-10V Dimming down to 1% No Dimming

Lens Frosted Flat (direct/indirect)

Mounting

Aircraft Cable (10' std) Note: For indirect distribution, mount at a minimum distance of 3ft from the ceiling

Wiring

Black and White 3 Conductor Wire (No Dimming) Black and White 5 Conductor Wire

Finishes

Black - RAL 9004, Grey - RAL 7046, White - RAL 9003 Custom RAL finishes available

Certifications cULus

Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.



delviro energy | All rights reserved. © delviro energy 1.877.502.3434 | info@delviro.com | delviro.com



Date	Fixture	Notes
Project		

Ordering Guide


Sample Configuration: ZIP CLOUD SQUARE - 18 - 40 - 40 - 80 - 4K - U - FR - DIRECT - WH - AC - DIMOFF - BFC 5 WIRE - CL - 6 - WH

ZIP CLOUD SQUARE		E	Size	Wa	atts: Direct	*Watts: Indirect (25" Model)		CRI	Color Temp	Voltage	FR	Distribution
Finish	AC Mount		Driver		Wiring	Wire Color	Wire	e Length	Canopy Finish			
Model	Size	Size Watts: Direct		Watts: Indirect			CRI	Color Temp	Voltage	L	_ens	
ZIP CLOUD SQUARE	18 25		20, 40 20, 40, 60	, 80	40* Note: Indirect Distribution for 25" Model Only			80 90	3K - 3000K 35K - 3500K 4K - 4000K 5K - 5000K	U - 120/27 H - 347V		FR - Frosted Flat direct/indirect)
Distribution Finish		Mounting		Driver W		Wiring	Wiring					
DIRECT/INDIRECT BLK GRY CU - Note finish		White - Black - Grey Custom* : For custon es please s number			on,	DIMOFF - 0-10V Dimming down to 1% ND - No Dimming		BFC 3 WIRE- Black 3 Conductor Wire (no dimming) WFC 3 WIRE - White 3 Conductor Wire (no dimming BFC 5 WIRE - Black 5 Conductor Wire WFC 5 WIRE - White 5 Conductor Wire				
Wire Color	Wir	re Leng	th	Canopy	Finish							
CL - Clear	L - Clear Length WH - W			WH - W	hite							

Wire Color	Wire Length	Canopy Finish	
CL - Clear Optional B - Black W - White	Length 6' Standard	WH - White BLK - Black CU - Custom* Note: Please contact factory for custom finishes	



Dimensions



H: 4.0″

Zip Cloud Square 25




W: 25" L: 25"


Output Performance

Model	Direct Watts	Direct Lm/W	Delivered Lumens	Indirect Watts	Indirect Lm/W	Delivered Lumens
Zip Cloud Square 18	20	107.5	2150			
	40	107.5	4300			
	20		2425	40	115	4600
Zin Cloud Square 05	40	101.05	4850			
Zip Cloud Square 25	60	121.25	7275			
	80		9700			

Mounting Points




Zip Cloud Square 18




Zip Cloud Square 25

Mounting Options



Aircraft Cable Canopy / Drywall Anchor



Finish Options

Standard Finishes



Custom Finishes



Please contact factory for additional and custom Finishes

Canopy Finishes

