

Date	Fixture	Project	Quantity
------	---------	---------	----------

# VTs

## Vapor Tight

### Features

- Weatherproof LED fixture
- Enclosed and gasketed body protects electronics from harsh weather elements
- 4' and 8' lengths
- Polycarbonate shatterproof housing
- Moisture, vapor, chemical resistant, corrosion free, and dust protective
- NSF available
- Designed and Manufactured in North America
- 5 Year Warranty



### Specifications

#### Construction

Polycarbonate, Shatterproof Housing  
 Stainless Steel Latches  
 IP 65 (Grey Body - Standard)  
 IP 67 (White Body - Custom Order)

#### Dimensions

VTs 4: 6"W x 50"L x 4.25"H  
 VTs 8: 6"W x 102"L x 4.25"H

#### LED

Samsung LM281B Plus Pro, 3-Step MacAdam Binning  
 200,000+ Life Hours (L70)

#### Efficacy

VTs 4: Up to 155 Lm/W  
 VTs 8: Up to 152 Lm/W

#### Watts

VT4s: 30W, 40W, 60W, 80W  
 VT8s: 40W, 60W, 80W, 120W

#### Color Temperature

3000K - 5000K

#### CRI

80 or 90

#### Voltage

120/277V or 347/480V

#### Controls

0-10V Dimming down to 1%

#### Operating Temperature

-40°C to +40°C | -40°F to +104°F  
 +55°C | +131°F - available

#### Lens

Frosted or Clear

#### Mounting

Aircraft Cable  
 Surface Mount Brackets  
 V-Clips

#### Accessories

Occupancy Sensor (on/off)  
 Waterproof Occupancy Sensor,  
 Bi-Level Dimming  
 Waterproof Bi-Level Dimming,  
 10kV Surge Protection  
 Emergency Battery

#### Wiring

Black or White Flexible Cord, Internal

#### Finishes

Grey  
 White - Custom

#### Certifications

DLC Premium  
 DLC  
 cULus

Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at [www.designlights.org/qpl](http://www.designlights.org/qpl).



## Ordering Guide

Sample Configuration: VT4s - 60 - 80 - 4K - U - FR - GRY - AC - BFC - N - IP65 - N

Model	Watts	CRI	Color Temp	Voltage	Lens	Finish	Mounting	Wiring	Accessories
Enclosure	NSF								

Model	Watts	CRI	Color Temp	Voltage	Lens	Finish	Mounting
<b>VT4s</b>	30, 40, 60, 80	80	3K - 3000K	U - 120/277V	FR - Frosted	GRY - Grey	AC - Aircraft Cable
<b>VT8s</b>	40, 60, 80, 120	90	35K - 3500K 4K - 4000K 5K - 5000K	H - 347/480V	CL - Clear	Optional WH - White*	BKTS - Surface Mount Brackets V - V Hooks
						Note: Custom order, consult factory	

Wiring	Accessories	Enclosure	NSF
BFC - Black Flexible Cord WFC - White Flexible Cord IN - Internal	N - None Optional OCC - Occupancy Sensor (on/off) BLD - Bi-Level Dimming (100%/10%) WBD - Waterproof Bi-Level Dimming (100%/10%) WOC - Waterproof Occupancy Sensor (on/off) 10kV - 10kV Surge Protection EM - Emergency Battery	IP65 - Standard (Grey Body) IP67 - White Body (Custom Order)	N - None NSF - White Body*  Note: Custom order, consult factory


Note: For custom configurations please contact factory

## Dimensions




W: 6.1"  
H: 4.25"

### VT4s



35.5"




50.0"

### VT8s



87.5"



102.0"

## Output Performance

Model	Watts	Lm/W	Delivered Lumens	Model	Watts	Lm/W	Delivered Lumens
VT4s 30	29.82	158.22	4718	VT8s 40	42.07	165.43	6960
VT4s 40	42.07	156.09	6567	VT8s 60*	64.84	164.87	10690
VT4s 60*	64.84	153.96	9983	VT8s 80*	78.25	164.30	12856
VT4s 80*	78.25	149.70	11715	VT8s 120*	117.38	163.17	19153

Note: \* DLC Premium