

Date	Fixture	Notes
Project		

Zip

Linear Strip Light

Features

- LED linear light fixture.
- Pendant and surface mounting options.
- 2', 4', and 8' lengths.
- Continuous run option.
- Enclosed lens prevents penetration of dust, insects, and other debris into the lamp compartment.
- Dry and damp rated.
- Designed and Manufactured in North America.



Specifications

Construction

Steel Housing
 Powder Coated Finish

Dimensions

Zip Round 2: 23.6"
 Zip Round 4: 46.1"
 Zip Round 8: 91.1"

LED

Samsung LM281B Plus Pro (3-Step
 MacAdam Binning)
 200,000+ Life Hours (L70)

Watts

Zip Round 2: 20W, 30W
 Zip Round 4: 20W - 100W
 Zip Round 8: 40W - 120W

Color Temperature

3000K - 5000K

CRI

80 or 90

Voltage

120/277V or 347V

Controls

0-10V Dimming down to 1%

Operating Temperature

-35°C to +45°C | -31°F to +113

Lens

Frosted
 Clear

Mounting

Aircraft Cable (10' std)
 V-Hooks
 Surface

Accessories

Occupancy Sensor (on/off)
 Ultrasonic Occupancy Sensor
 Bi-Level Dimming - Programmable
 (100%/10%)
 Emergency Battery
 10kV Surge Protection
 Microwave Sensor -External (with BLD
 and Daylight Harvesting options)

Wiring

Black or White Flexible Cord
 Internal

Finishes

White - RAL 9003
 Antimicrobial Powder Coating

Certifications

cULus

Warranty

5-Year Warranty



Ordering Guide

Sample Configuration: ZIP - 4 - 60 - 80 - 4K - U - FR - WH - AC - BFC - N - RND


ZIP							WH		
Model	Length	Watts	CRI	Color Temp	Voltage	Lens	Finish	Mounting	Wiring
	RND								
Accessories	Type								

Model	Length	Watts	CRI	Color Temp	Voltage	Lens	Finish
ZIP	2	20, 30	80	3K - 3000K	U - 120/277V	FR - Frosted	WH - White
	4	20, 30, 40, 60, 80, 100	90	35K - 3500K	H - 347V	Optional	AM - Antimicrobial Powder Coating
	8	40, 60, 80, 100, 120		4K - 4000K 5K - 5000K		CL - Clear	


Mounting	Wiring	Accessories	TYPE
AC - Aircraft Cable 6' std V - V Hooks SU - Surface Optional CR - Continuous Run	IN - Internal BFC - Black Flexible Cord WFC - White Flexible Cord	N - None Optional OCC - Occupancy Sensor (on/off) UOCC - Ultrasonic Occupancy Sensor BLD - Bi-Level Dimming - Programmable (100%/10%) EM - Emergency Battery 10kV - 10kV Surge Protection MICRO - Microwave Sensor -External (with BLD and Daylight Harvesting options)	RND

Note: For custom configurations please contact factory


Dimensions



W: 6.01"
H: 3.58"



2': 23.6"



4': 46.1"




8': 91.1"

Output Performance at 4K

Model	Watts	Lm/W	Delivered Lumens
Zip Rnd 4 20	18.9	131.3	2477
Zip Rnd 4 30	30	131.3	3939
Zip Rnd 4 40	37.7	131.3	4954
Zip Rnd 4 60	60	131.3	7878
Zip Rnd 4 80	75.5	131.3	9907
Zip Rnd 4 100	100	131.3	13130

Photometrics



Zip 4-100, 4K
Frosted Lens

ZONAL LUMEN SUMMARY

Zone	Lumens	% of Fixture
0° - 30°	3842	26%
0° - 60°	10818	73%
0° - 90°	14325	96%
90° - 120°	523	4%
90° - 150°	565	4%
90° - 180°	565	4%
0° - 180°	14890	100%
20° - 50°	6821	46%

ZONAL LUMEN SUMMARY

Zone	Lumens	Zone	Lumens
0° - 10°	478	100° - 110°	147
10° - 20°	1346	110° - 120°	63
20° - 30°	2018	120° - 130°	26
30° - 40°	2382	130° - 140°	11
40° - 50°	2422	130° - 140°	4
50° - 60°	2173	150° - 160°	1
60° - 70°	1709	160° - 170°	0
70° - 80°	1150	1170° - 180°	0
80° - 90°	648		
90° - 100°	313		