


Date	Fixture	Quantity	Project
------	---------	----------	---------



DTL Curve Pendant

Features

- Architectural luminaire. Contemporary and minimal design
- Pendant mounting
- Direct, direct/indirect, indirect distribution options
- 5ft radius
- Continuous run option
- Multiple finishes
- Dry and damp rated for indoor applications
- Designed and Manufactured in North America
- 5 Year Warranty

Specifications

Construction

Aluminum Extruded Body
Cast End Caps with Light Block
Powder Coated Finish

Dimensions

Widths: 3.18"
Height: 4.125"
Length: 48"

LED

Samsung LM281B Plus Pro, 3-Step MacAdam Binning
4000K - 130 Lm/W, 3500K - 98%, 3000K - 95%
2700K-5000K
CRI 80 | 90
L90>70,000
CRI: 80, 90

Lumens/Ft - Direct/Indirect

Min: 250 Lm/ft - Max: 1200 Lm/ft

Voltage

120/277V or 347V
Emergency Battery

Dimming(Driver)

0-10V Dimming down to 1%, DALI, Lutron, Philips SR, ELDO

Lens

Frosted flat(Direct/Indirect)

Mounting

Aircraft Cable 10' Standard
Note: For Indirect distribution, mount at a minimum distance of 3' from the ceiling

Finishes

RAL: Black, Grey, White(standard)
Custom RAL finishes available

Certifications

cULus

Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.



Ordering Guide

Sample Configuration: DTL CRV - C - 8 - D 500 - I 500 - 80 - 4K - U - FR - WH - AC - DIMOFF - N - 2 - N - 5WIRE - CL - 6 - WH

DTL CRV								FR		AC	
Model	Connection	CR	Direct Lm/Ft	Indirect Lm/Ft	CRI	Color Temp	Voltage	Lens	Finish	Mounting	Dimming
Controls	Circuits	Accessories	Wiring	Wire Color	Wire Length	Canopy Finish					

Model	Connection	CR - Continuous Run/Sections	Direct Lm/Ft	Indirect Lm/Ft	CRI
DTL CRV	C S	CR: _____ Continuous Run - Specify number of sections	D - 50 (min) - 1200 (max)	I - 250 (min) - 1200 (max)	80 90


Color Temp	Voltage	Lens	Finish	Mounting
27K - 2700K 3K - 3000K 35K - 3500K 4K - 4000K 5K - 5000K	U - 120/277V H - 347V	FR - Frosted Flat (direct/indirect)	WH - White BLK - Black GRY - Grey CU - Custom* Note: For custom finishes please specify RAL number	AC - Aircraft Cable (10' std) Note: For indirect distribution, mount at a minimum distance of 3ft from the ceiling

Dimming(Driver)	Controls	Circuits	Accessories
DIMOFF - 0-10V Dimming down to 1% Optional DALI - Digital Addressable Lighting Interface LUTRON - Lutron Ecosystem SR - Philips SR ELDO - Dim to 0.11% ELDO (347 only 1-10 5%)	N - None Optional SNS- Philips SNS 300 w/BLD & Daylight CLM - Encelium CLM LG - LG Dongle BT - Bluetooth Mesh EN - Enlighted Integral	1 - 1 Circuit 2 - 2 Circuit (direct/indirect)	N - None Optional 10kV - 10kV Surge Protection EM - Emergency Battery (5 or 6 Wire)* +GTD - Generator Transfer Device Note: EM - Emergency Battery, direct distribution only


Wiring	Wire Color	Wire Length	Canopy Finish
5 WIRE - Standard + EM Optional 6 WIRE - Emergency Battery w/ constant & switched HOT (Powercord: Black or White) N - 5 Leads	CL - Clear Optional B - Black W - White	Length _____ 6' Standard	WH - White BLK - Black CU - Custom* Note: Please contact factory for custom finishes

Distribution/Lens Options

Direct/Indirect Distribution




Lambertian
Direct: Frosted Flat Lens




Lambertian
Indirect: Frosted Flat Lens

Dimensions




W: 3.18"
H: 4.125"




Note: End Cap Thickness=0.1".
Add additional two End Cap thickness of 0.2" to length

Mounting




Aircraft Cable Canopy / Drywall Anchor

Connection Type




C-Connect




S-Connect


Sample Configurations




8x4' Section
Circle



4x4' Section
1/2 Circle




2x4' Section
1/4 Circle



4' Section
Linear Shapes

RAL Finish Options

Standard Finishes



Sample Custom Finishes



Additional RAL Finishes - Please Contact Factory



Canopy Finishes

