



Date: _____ Fixture: _____

Qty: _____ Project: _____



Zip Linear Luminaire

LED Luminaire. 2', 4', and 8' length options. High impact acrylic lens. Wall mountable option. Screw in LED pan single ground screw for easy installation. Enclosed lens prevents penetration of dust, insects, and other debris into the lamp compartment. Dry and Damp rated. DLC Listed. cULus listed. 10 Year Warranty.

Ordering Options

Model	Length	Watts	Color Temp	Voltage	Lens	Finish	Mounting
Zip	2	15, 20, 30	3K 3000K	U 120/277V	FR Frosted	WH White	V V Hooks
	4	15, 20, 30, 40, 60, 80, 100	35K 3500K	H 347V	CL Clear		SM Surface Mount
	8	40, 60, 80, 100, 120	4K 4000K				
			5K 5000K				
ZIP					WH		

Wiring	Accessories	Plug Options
BFC Black Flexible Cord WFC White Flexible Cord IN Internal 5WIRE 5 Wire	N None OCC Occupancy Sensor (on/off) UOCC Ultrasonice BLD Sensor BLD Bi Level Dimming (100%/10%) - Programmable MICRO Microwave Sensor EMBAT Emergency Battery 10kV 10kV Surge Protection	N None Plug See Plug Options Below

Sample: ZIP-4-60-4K-U-FR-WH-V-BFC-N-N

Plug Options

5-15P 125V 15A T Slot Plug	6-20P 250V AC 20A Plug	24-20P 347V AV 20A 3W/2P Plug NEMA 24-20
L5-15P 125V 15A Locking Plug	L6-20P 250V 20A Locking Plug	L24-20P 347V 20A Locking Plug
5-20P 125V AC 20A T-Slot Plug	7-15P 277V 15A 3W/2P NEMA 7-15 Plug	24-15P 347V AC 15A 3W/2 Plug NEMA 24-15
L5-20P 125V 20A Locking Plug	L7-15P 277V 15A Locking Plug	
6-15P 250V AC 15A 3W/2P Plug NEMA 6-15	7-20P 277V AC 20A Plug	
L6-15P 250V 15A Locking Plug	L7-20P 277V 20A Locking Plug	

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Product Specifications

Efficacy:	Zip 2: Up to 136 Lm/W Zip 4: Up to 140 Lm/W Zip 8: Up to 156 Lm/W
CRI:	86
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347V
Operating Temperature:	-35°C to +45°C -31°F to +113°F
Controls:	0-10V Dimming
Mounting:	V Hook, Flush Mount
Accessories:	Occupancy Sensor(on/off), Ultrasonic BLD Sensor, Bi-Level Dimming (100%/1%), Microwave Sensor, Emergency Battery, 10kV Surge Protection

Output Performance

Model	Input Watts	Lm/W	Delivered Lumens
Zip 2 15	13.65	134.5	1,836
Zip 2 20	22.1	135.1	2,999
Zip 2 30	30.67	135.7	4,161


Model	Input Watts	Lm/W	Delivered Lumens
Zip 4 15	15	140	1,766
Zip 4 20	20.3	140	2,885
Zip 4 30	29.8	140	4,003
Zip 4 40	41.6	140	5,378
Zip 4 60	59.7	140	8,272
Zip 4 80	79	140	11,060
*Zip 4 100	97.8	139	13,659

Note: Zip 4 100 - 120/277V

Model	Input Watts	Lm/W	Delivered Lumens
Zip 8 40	38	156	5,911
Zip 8 60	57	156	8,765
Zip 8 80	75	155	11,602
*Zip 8 100	99.2	155	15,400
Zip 8 120	116	152	17,830

Note: Zip 8 100 - 120/277V

Photometrics



Zip 4 40

Candle Power Summary

Along	22.5	45	67.5	Across	Output Lumens	Angle	Zone	Lumens	% Lamp	% Luminaire
1575	1575	1575	1575	1575		0	0-30	1200	27.07	27.07
1560	1568	1562	1570	1576	151	5	0-40	1930	43.55	43.55
1485	1498	1499	1507	1516	422	15	0-60	3296	74.36	74.36
1336	1350	1365	1380	1390	637	25	0-90	4291	96.80	96.80
1125	1144	1174	1198	1209	731	35	40-90	2361	53.26	52.26
877	903	952	990	1003	729	45	60-90	994	22.44	22.44
624	657	732	770	785	637	55	90-180	141	3.20	3.20
392	430	504	559	557	490	65	0-180	4434	100.00	100.00
199	240	317	373	391	325	75				
52	98	175	229	245	179	85				
0	51	122	172	187	83	90				
0	22	80	125	139	35	95				
0	3	31	60	71	14	105				
0	1	11	27	33	6	115				
0	0	5	13	16	2	125				
0	0	2	6	7	1	135				
0	0	0	3	3	0	145				
0	0	0	0	0	0	155				
0	0	0	0	0	0	165				
0	0	0	0	0	0	175				
0	0	0	0	0	0	180				

Electrical Consumption

Input Voltage: 120 VRMS
 Input Voltage: 0.328 ARMS
 Input Voltage: 38.92
 Input Voltage: 0.989

Dimensions

