



Date: _____ Fixture: _____

QTY: _____ Project: _____



Zip Cloud

Pendant | Flush Mount

Contemporary design. Powder coated aluminum extrusion. Seamless body. Suspended and flush mount options. Direct distribution. 200,000 hr+ L70 w/Samsung LEDs. cULus Listed.

Designed and manufactured in North America. 10 Year Warranty



Ordering Options

Model	Size	Watts	CRI	Color Temp	Voltage	Distribution	Finish
ZIP CLOUD	18	18: 20, 40, 60, 70	80	3K 3000K	U 120/277V	DIRECT Direct	WH White
	24	24: 20, 40, 60, 80	90	35K 3500K	H 347V		CU Custom <i>(consult factory)</i>
	36	36: 40, 80, 120, 160		4K 4000K			
	44	44: 80, 120, 160		5K 5000K			

ZIP CLOUD DIRECT

Mounting	Wiring	Accessories	Canopy Finish
AC Aircraft Cable	BFC 3 WIRE Black 3 Conductor Wire _____	10D 0-10V Dimming	WH White
FM Flush Mount	BFC 5 WIRE Black 5 Conductor Wire _____	DIMOFF 0-10 1% Dim to off Driver	CU Custom <i>(consult factory)</i>
	WFC 3 WIRE White 3 Conductor Wire _____		
	WFC 5 WIRE White 5 Conductor Wire _____		
	GFC Grey Flexible Cord <i>(consult factory)</i>		
	N None		

Sample Configuration: ZIP CLOUD - 18 - 40 - 4K - U - DIRECT - WH - AC - BFC 3 WIRE - 10D - WH

Specifications

Efficacy:	120 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347/480V
Operating Temperature:	-20°C to +40°C -4°F to +104°F
Mounting:	Aircraft Cable, Surface Mount
Accessories:	0-10V Dimming, 0-10 1% Dim to off driver

Output Performance

Model	Watts	Lm/W	Delivered Lumens
Zip Cloud 18	20	120 Lm/W	2,400
	40		4,800
	60		7,200
	70		8,400
Zip Cloud 24	20	120 Lm/W	2,400
	40		4,800
	60		7,200
	80		9,600
Zip Cloud 36	40	120 Lm/W	4,800
	80		9,600
	120		14,400
	160		19,200
Zip Cloud 44	80	120 Lm/W	9,600
	120		14,400
	160		19,200

Dimensions

