



Date: \_\_\_\_\_ Fixture: \_\_\_\_\_

QTY: \_\_\_\_\_ Project: \_\_\_\_\_



## TitanHB 160 High Bay with Recessed Kit

Titan recessed fixture. Aluminum construction with polycarbonate protective lens. The perfect LED solution for industrial, commercial, warehouses, and large box retail applications.

DLC Listed. cULus listed.

Designed and manufactured in North America.

5 Year Warranty.

### Ordering Options

Model	Watts	CRI	Color Temp	Voltage	Lens	Finish	Mounting
TITANHB	160	80 90	3K 3000K	U 120/277V	FR Frosted	WH White	TG T-Grid
			35K 3500K	H 347V	CL Clear	CU Custom - (consult factory)	
			4K 4000K				
			5K 5000K				
TITANHB	160						TG

#### Wiring

- BFC** Black Flexible Cord
- WFC** White Flexible Cord
- IN** Internal

#### Accessories

- N** None
- OCC** Occupancy Sensor(on/off)
- WC** Wireless Controls - (consult factory)
- BLD** Bi-Level Dimming(100%/10%)
- GCC** Gasketed and Conformal Coated
- DA** Dimming Wire Accessible
- 10kV** 10kV Surge Protection

Sample Configuration: TITANHB - 160 - 4K - U - FR - WH - TG - BFC - N - N

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at [www.designlights.org/qpl](http://www.designlights.org/qpl).

### Product Specifications

- Efficacy:** 126.1Lm/W
- CRI:** 80 | 90
- Color Temperature:** 3000K, 3500K, 4000K, 5000K
- Lumen Maintenance:** 200,000+ Life Hours (L70)
- Voltage:** 120/277V | 347/480V
- Operating Temperature:** -40°C to +40°C | -40°F to +104°F
- Controls:** 0-10V Dimming
- Mounting:** T-Grid
- Accessories:** Occupancy Sensor (on/off), Wireless Controls, Bi-Level Dimming (100%/10%), 10kV Surge Protection, Dimming Wire, Emergency Battery, Gasketed and Conformal Coated

### Output Performance

Model	Watts	Lm/W	Delivered Lumens
TitanHB 160	159	126.1	20,048

### Dimensions

