



Intertek

Date: _____ Fixture: _____

QTY: _____ Project: _____



Troffer 1x4 Retrofit Kit

1x4 LED troffer retrofit. 18 gauge aluminum. Easy installation with little maintenance. High gloss white finish. Offices, conference rooms, corridors, classrooms, hallways, cafeterias, retail, and general floor lighting applications.

DLC listed. cETLus listed.

Designed and manufactured in North America.

5 Year Warranty.

Ordering Options

Model	Watts	CRI	Color Temp	Voltage	Finish	Mounting
TRFT2 1x4	15	80	3K 3000K	U 120/277V	WH White	RT Retrofit
	20	90	35K 3500K	H 347V		
	30		4K 4000K			
	40		5K 5000K			
	60					
TRFT2 1x4					WH	RT

Sample Configuration: TRFT2 1x4 - 15 - 80 - 4K - U - WH - RT

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Product Highlights

Efficacy:	LW9 Lens: Up to 115 Lm/W K12 Lens: Up to 137 Lm/W No Lens: Up to 155 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	150,000+ Life Hours (L70)
Voltage:	120/277V 347V
Operating Temperature:	-40°C to +40°C -40°F to +104°F
Controls:	0-10V Dimming

Output Performance

Model	Input Watts	With LW9 Lens		With K12 Lens		No Lens	
		Lm/W	Delivered Lumens	Lm/W	Input Watts	Lm/W	Delivered Lumens
TRFT2 1x4 15*	13.9	115.1	1,601	137	1,904	155	2,155
TRFT2 1x4 20	21.6	112.5	2,434	134	2,894	153	3,305
TRFT2 1x4 30	30.9	104.7	3,242	126	3,893	144.7	4,471
TRFT2 1x4 40	40.3	100.4	4,050	122	4,917	140	5,642
TRFT2 1x4 60	60.1	98	5,831	120	7,212	138	8,294

Note: TRFT2 1x4 15 - 120/277V Only, Lens not supplied

Dimensions

