



Intertek

Date: \_\_\_\_\_ Fixture: \_\_\_\_\_

QTY: \_\_\_\_\_ Project: \_\_\_\_\_



## Troffer 2x2 Retrofit Kit

2x2 LED troffer retrofit. 18 gauge aluminum. Easy installation with little maintenance. High gloss white finish. Offices, conference rooms, corridors, classrooms, hallways, cafeterias, retail, and general floor lighting applications.

DLC listed. cETLus listed.

Designed and manufactured in North America.

5 Year Warranty.

### Ordering Options

Model	Watts	CRI	Color Temp	Voltage	Finish	Mounting
TRFT2 2x2	15	80	3K 3000K	U 120/277V	WH White	RT Retrofit
	20	90	35K 3500K	H 347V		
	30		4K 4000K			
	40		5K 5000K			
	60					
TRFT2 2x2					WH	RT

Sample Configuration: TRFT2 2x2 - 15 - 80 - 4K - U - WH - RT

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at [www.designlights.org/qpl](http://www.designlights.org/qpl).

### Product Highlights

- Efficacy:** Up to 114 Lm/W
- CRI:** 80 | 90
- Color Temperature:** 3000K, 3500K, 4000K, 5000K
- Lumen Maintenance:** 150,000+ Life Hours (L70)
- Voltage:** 120/277V | 347V
- Operating Temperature:** -40°C to +40°C | -40°F to +104°F
- Controls:** 0-10V Dimming

### Output Performance

Model	Watts	Lm/W	Delivered Lumens
TRFT2 2x2 15	13.9	100.5	1,399
TRFT2 2x2 20	21.5	96.6	2,082
TRFT2 2x2 30	31.4	109.1	3,430
TRFT2 2x2 40	36.5	114.2	4,175
TRFT2 2x2 60	58.9	112.9	6,655

### Dimensions

