



Intertek

Date: _____ Fixture: _____

QTY: _____ Project: _____



Troffer 2x4 Retrofit Kit

2x4 LED troffer retrofit. 18 gauge aluminum. Easy installation with little maintenance. High gloss white finish. Offices, conference rooms, corridors, classrooms, hallways, cafeterias, retail, and general floor lighting applications.

DLC listed. cETLus listed.

Designed and manufactured in North America.

5 Year Warranty.

Ordering Options

Model	Watts	CRI	Color Temp	Voltage	Finish	Mounting
TRFT2 2x4	30	80	3K 3000K	U 120/277V	WH White	RT Retrofit
	40	90	35K 3500K	H 347V		
	60		4K 4000K			
	80		5K 5000K			
	120					
TRFT2 2x4					WH	RT

Sample Configuration: TRFT2 2x4 - 30 - 80 - 4K - U - WH - RT

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Product Highlights

Efficacy: Up to 117 Lm/W
CRI: 83+
Color Temperature: 3000K, 3500K, 4000K, 5000K
Lumen Maintenance: 150,000+ Life Hours (L70)
Voltage: 120/277V | 347V
Operating Temperature: -40°C to +40°C | -40°F to +104°F
Controls: 0-10V Dimming

Output Performance

Model	Watts	Lm/W	Delivered Lumens
TRFT2 2x4 30	27.9	117.1	3,270
TRFT2 2x4 40	38.2	116.4	4,446
TRFT2 2x4 60	57.6	110.3	6,361
TRFT2 2x4 80	77.9	106.2	8,276
TRFT2 2x4 120	120	110	13,200

Dimensions

