



Date: \_\_\_\_\_ Fixture: \_\_\_\_\_

QTY: \_\_\_\_\_ Project: \_\_\_\_\_



## Zip Cloud Suspended Direct

Contemporary design. Powder coated aluminum extrusion. Seamless body. Suspended and flush mount options. Direct distribution. 200,000 hr+ L70 w/Samsung LEDs. cULus Listed.

Designed and manufactured in North America.  
5 Year Warranty

### Ordering Options

Model	Size	Watts	CRI	Color Temp	Voltage	Distribution	Finish
ZIP CLOUD	18	20, 40, 60, 70	80	3K 3000K	U 120/277V	DIRECT Direct	WH White
	24	20, 40, 60, 80	90	35K 3500K	H 347V		CU Custom ( <i>consult factory</i> )
	36	40, 80, 120, 160		4K 4000K			
	44	80, 120, 160		5K 5000K			

ZIP CLOUD       DIRECT

Mounting	Wiring	Accessories	Canopy Finish
AC Aircraft Cable	<b>BFC 3 WIRE</b> Black 3 Conductor Wire _____ <b>BFC 5 WIRE</b> Black 5 Conductor Wire _____ <b>WFC 3 WIRE</b> White 3 Conductor Wire _____ <b>WFC 5 WIRE</b> White 5 Conductor Wire _____ <b>GFC</b> Grey Flexible Cord ( <i>consult factory</i> ) <b>N</b> None	<b>10D</b> 0-10V Dimming <b>DIMOFF</b> 0-10 1% Dim to off Driver	<b>WH</b> White <b>CU</b> Custom ( <i>consult factory</i> )

AC

Sample Configuration: ZIP CLOUD - 18 - 40 - 4K - U - DIRECT - WH - AC - BFC 3 WIRE - 10D - WH

## Specifications

<b>Efficacy:</b>	120 Lm/W
<b>CRI:</b>	80   90
<b>Color Temperature:</b>	3000K, 3500K, 4000K, 5000K
<b>Lumen Maintenance:</b>	200,000+ Life Hours (L70)
<b>Voltage:</b>	120/277V   347/480V
<b>Operating Temperature:</b>	-20°C to +40°C   -4°F to +104°F
<b>Mounting:</b>	Aircraft Cable
<b>Accessories:</b>	0-10V Dimming, 0-10 1% Dim to off driver

## Output Performance

Model	Watts	Lm/W	Delivered Lumens
Zip Cloud 18	20	120	2,400
	40		4,800
	70		7,200
Zip Cloud 24	20	120	2,400
	40		4,800
Zip Cloud 36	40	120	4,800
	80		9,600
	120		14,400
	160		19,200
Zip Cloud 44	80	120	9,600
	120		14,400
	160		19,200

## Dimensions

