



Date: _____ Fixture: _____

QTY: _____ Project: _____



Zip Cloud Recessed

Contemporary design. Powder coated aluminum extrusion. Seamless body. Recessed lighting. 200,000 hr+ L70 w/Samsung LEDs. cULus Listed.

Designed and manufactured in North America.
5 Year Warranty

Ordering Options

Model	Size	Watts	CRI	Color Temp	Voltage	Finish
ZIP CLOUD RECESSED	18	18: 20, 40, 60, 70	80	3K 3000K	U 120/277V	WH White
	24	24: 20, 40, 60, 80	90	35K 3500K	H 347V	CU Custom (<i>consult factory</i>)
	36	36: 40, 80, 120, 160		4K 4000K		
	44	44: 80, 120, 160		5K 5000K		

ZIP CLOUD RECESSED

Wiring

- BFC 3 WIRE** Black 3 Conductor Wire _____
- BFC 5 WIRE** Black 5 Conductor Wire _____
- WFC 3 WIRE** White 3 Conductor Wire _____
- WFC 5 WIRE** White 5 Conductor Wire _____
- GFC** Grey Flexible Cord (*consult factory*)
- N** None

Accessories

- 10D** 0-10V Dimming
- DIMOFF** 0-10 1% Dim to off Driver

Sample Configuration: ZIP CLOUD RECESSED - 18 - 40 - 80 - 4K - U - Direct - WH - AC - BFC 3 WIRE - 10D - WH

Specifications

Efficacy:	120 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347/480V
Operating Temperature:	-20°C to +40°C -4°F to +104°F
Mounting:	Recessed
Accessories:	0-10V Dimming, 0-10 1% Dim to off driver

Output Performance

Model	Watts	Lm/W	Delivered Lumens
Zip Cloud 18	20	120	2,400
	40		4,800
	70		8,400
Zip Cloud 24	20	120	2,400
	40		4,800
Zip Cloud 36	40	120	4,800
	80		9,600
	120		14,400
	160		19,200
Zip Cloud 44	80	120	9,600
	120		14,400
	160		19,200

Dimensions

