



Date: \_\_\_\_\_ Fixture: \_\_\_\_\_

QTY: \_\_\_\_\_ Project: \_\_\_\_\_



# Zip Flat

## Linear Luminaire

LED Luminaire. 4' and 8' length options. 3' option available (consult factory). Steel construction. Frosted flat acrylic lens. Wall mountable option. Continuous run option. Enclosed lens prevents penetration of dust, insects, and other debris into the lamp compartment. Dry and Damp rated.

DLC Listed. cULus listed.  
Designed and manufactured in North America.  
5 Year Warranty.

### Ordering Options

Model	Watts	CRI	Color Temp	Voltage	Lens	Finish	Mounting
ZIP 4	15, 20, 30, 40, 60	80	3K 3000K	U 120/277V	FRFL Frosted Flat	WH White CUBLK Custom Black - (consult factory)	V V Hooks FM Flush Mount CR Continuous Run
ZIP 8	40, 60, 80, 100, 120	90	35K 3500K	H 347V			
CU 96"			4K 4000K 5K 5000K				

Wiring	Accessories	Type
BFC Black Flexible Cord	N None	FLT Flat
WFC White Flexible Cord	OCC Occupancy Sensor (on/off)	
IN Internal	MICRO Microwave Sensor	
	EM Emergency Battery	
	10kV 10kV Surge Protection	

Sample Configuration: Zip - 8 - 60 - 90 - 4K - U - FRFL - WH - V - BFC - N - FLT

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at [www.designlights.org/qpl](http://www.designlights.org/qpl).

## Product Specifications

<b>Efficacy:</b>	Zip 4: 140 Lm/W   Zip 8: Up to 156 Lm/W
<b>CRI:</b>	80   90
<b>Color Temperature:</b>	3000K, 3500K, 4000K, 5000K
<b>Lumen Maintenance:</b>	200,000+ Life Hours (L70)
<b>Voltage:</b>	120/277V   347V
<b>Operating Temperature:</b>	-35°C to +45°C   -31°F to +113°F
<b>Controls:</b>	0-10V Dimming (347)
<b>Mounting:</b>	V Hook, Flush Mount, Continuous Run
<b>Accessories:</b>	Occupancy Sensor(on/off), Microwave Sensor, Emergency Battery, 10kV Surge Protection

## Output Performance

Model	Watts	Lm/W	Delivered Lumens	Model	Watts	Lm/W	Delivered Lumens
Zip 4 15	15	140	1,766	Zip 8 40	38	156	5,911
Zip 4 20	20.3	140	2,885	Zip 8 60	57	156	8,765
Zip 4 30	29.8	140	4,003	Zip 8 80	75	155	11,602
Zip 4 40	41.6	140	5,378	Zip 8 100	99.2	155	15,400
Zip 4 60	59.7	140	8,272	Zip 8 120	116	152	17,830

## Dimensions

