



Date: _____ Fixture: _____

QTY: _____ Project: _____



Zip Square Linear Luminaire

LED linear. 2', 4, and 8' length options. Square profile. Wall mountable option. Polycarbonate and acrylic lens options. Enclosed lens prevents penetration of dust, insects, and other debris into the lamp compartment. Dry and damp rated.

DLC Listed. cULus listed.
Designed and manufactured in North America.
5 Year Warranty.

Ordering Options

Model	Length	Watts	CRI	Color Temp	Voltage	Lens	Finish	Mounting
ZIP	2	15, 20, 30	80	3K 3000K	U 120/277V	FR Frosted	WH White	V V Hooks
	4	15, 20, 30, 40, 60, 80, 100	90	35K 3500K	H 347V	CL Clear		FM Flush Mount
	8	40, 60, 80, 100, 120, 160		4K 4000K 5K 5000K		PC Polycarbonate		CR Continuous Run
ZIP							WH	

Wiring

BFC Black Flexible Cord
WFC White Flexible Cord
IN Internal

Accessories

N None
OCC Occupancy Sensor (on/off)
UOCC Ultrasonic BLD Sensor
EM Emergency Battery
10kV 10kV Surge Protection
MICRO Integral Programmable Microwave Sensor

Sample Configuration: Zip - 8 - 60 - 80 - 4K - U - FR - WH - V - BFC - N - SQ

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Product Specifications


Efficacy:	Zip 2: Up to 136 Lm/W Zip 4: Up to 140 Lm/W Zip 8: Up to 156 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347V
Operating Temperature:	-35°C to +45°C -31°F to +113°F
Controls:	0-10V Dimming
Mounting:	V Hook, Flush Mount
Accessories:	Occupancy Sensor(on/off), Ultrasonic BLD Sensor, Integral Programmable Microwave Sensor, Emergency Battery, 10kV Surge Protection

Output Performance

Model	Watts	Lm/W	Delivered Lumens	Model	Watts	Lm/W	Delivered Lumens
Zip 2 15	13.65	134.5	1,836	Zip 8 40	38	156	5,911
Zip 2 20	22.1	135.1	2,999	Zip 8 60	57	156	8,765
Zip 2 30	30.7	135.7	4,161	Zip 8 80	75	155	11,602
				* Zip 8 100	99.2	155	15,400
				Zip 8 120	116	152	17,830
				<i>Note: Zip 8 100 - 120/277V Only</i>			
Model	Watts	Lm/W	Delivered Lumens				
Zip 4 15	15	140	1,766				
Zip 4 20	20.3	140	2,885				
Zip 4 30	29.8	140	4,003				
Zip 4 40	41.6	140	5,378				
Zip 4 60	59.7	140	8,272				
Zip 4 80	79	140	11,060				
Zip 4 100	97.8	139	13,659				

Note: Zip 4 100 - 120/277V Only

Dimensions



2': 23.75" | 4': 47.75" | 8': 95.75"

