



Date: \_\_\_\_\_ Fixture: \_\_\_\_\_

QTY: \_\_\_\_\_ Project: \_\_\_\_\_



## Zoom High Bay

Energy efficient LED luminaire. Suspended mounting. Architectural, retail, industrial, and commercial high bay applications. Aluminum construction. White finish. Custom finishes available. Aluminum and acrylic reflector options. DLC listed. cULus listed. 5 Year Warranty.

### Ordering Options

Model	Watts	CRI	Color Temp	Voltage	Dome Type	Finish	Mounting
<b>ZOOM</b>	<b>50</b>	<b>80</b>	<b>3K</b> 3000K	<b>U</b> 120/277V	<b>16AC</b> 16 Clear Acrylic	<b>WH</b> White	<b>H</b> Hook
	<b>70</b>	<b>90</b>	<b>35K</b> 3500K	<b>H</b> 347V	<b>16AL</b> 16 Aluminum	<b>CU</b> Custom ( <i>consult factory</i> )	
	<b>90</b>		<b>4K</b> 4000K				
	<b>120</b>		<b>5K</b> 5000K				
	<b>150</b>						
	<b>180</b> <b>195</b>						
<b>ZOOM</b>							<b>H</b>

Wiring	Accessories	Lens	CRI (Standard / HD)
<b>BFC</b> Black Flexible Cord <b>WFC</b> White Flexible Cord	<b>N</b> None <b>DA</b> Dimming Wire Accessible <b>10kV</b> 10kV Surge Protection <b>DIMOFF</b> 0-10% Dim to off Driver	<b>NL</b> No Lens <b>CLD</b> Clear Diffused	<b>ST</b> Standard <b>HD</b> High Definition

Sample Configuration: ZOOM - 70 - 80 - 4K - U - 16AL - WH - H - BFC - N - NL - ST

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at [www.designlights.org/qpl](http://www.designlights.org/qpl).

## Product Highlights

<b>Efficacy:</b>	Up to 138 Lm/W
<b>CRI:</b>	80   90
<b>Color Temperature:</b>	3000K, 3500K, 4000K, 5000K
<b>Lumen Maintenance:</b>	75,000+ Life Hours (L70)
<b>Voltage:</b>	120/277V
<b>Operating Temperature:</b>	-40°C to +50°C   -40°F to +122°F
<b>Controls</b>	0-10V Dimming
<b>Mounting:</b>	Hook
<b>Accessories:</b>	Dimming Wire Accessible, 10kV Surge Protection, 0-10% Dim to off Driver

## Output Performance

Model	Watts	Lm/W	Delivered Lumens
Zoom 50	50	125	6,250
Zoom 70	75.6	138.1	10,709
Zoom 90	87.4	132.9	11,617
Zoom 120	120.1	114.7	15,405
Zoom 150	152.3	122.9	18,722
Zoom 180	178.7	121	21,623
Zoom 195	199.8	119.7	23,911

## Dimensions

