



Date: _____ Fixture: _____

QTY: _____ Project: _____



Zip Cloud Ring

Suspended Direct | Direct-Indirect

Contemporary design. Powder coated aluminum extrusion. Seamless body. Suspended and flush mount options. Direct distribution. 200,000 hr+ L70 w/Samsung LEDs. cULus Listed.

Designed and manufactured in North America.
5 Year Warranty

Ordering Options

Model	Size	Direct Watts/Ft	Indirect Watts/Ft	CRI	Color Temp	Voltage	Lens
ZIP CLOUD RING 3.18	24	2.5W	2.5W	80	3K 3000K	U 120/277V	FR Frosted
	36	5W	5W	90	35K 3500K		
	44	7W	7W		4K 4000K		
	60	10W	10W		5K 5000K		
	72						
	96						

ZIP CLOUD RING 3.18						U	FR
---------------------	--	--	--	--	--	---	----

Finish	Mounting	Wiring	Accessories
WH White BLK Black CU Custom (<i>consult factory</i>)	AC Aircraft Cable	BFC 5 WIRE Black 5 Conductor Wire WFC 5 WIRE White 5 Conductor Wire	DIMOFF 0-10 1% Dim to off Driver ENCILUM CLM ENLIGHTED OTHER Additional Accessories (<i>consult factory</i>)
	AC		

Sample Configuration: ZIP CLOUD RING 3.18 - 18 - 2.5W - 2.5W - 90 - 4K - U - FR - WH - AC - 5WIRE - DIMOFF

Specifications

Efficacy:	100 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V
Controls:	0-10V Dimming
Mounting:	Aircraft Cable,
Accessories:	0-10V 1% Dim to Off Driver, Encilium, Enlighted, Additional (<i>contact factory</i>)

Output Performance

Distribution	Watts/Ft	Delivered Lumens	Distribution	Watts/ft	Delivered Lumens
Direct	2.5	250	Indirect	2.5	250
	5	500		5	500
	7.5	750		7.5	750
	10	1000		10	1000

Dimensions

