

Fixture: _____ QTY: _____ Project : _____

Thinline U 120


Suspended

Direct | Direct-Indirect

Architectural luminaire. 120° U Shaped luminaire. Pendant mounting.
 Direct and direct-indirect distribution options. Available in 2 sizes.
 2.25" wide. Multiple finishes available.

cULus Listed

Designed and manufactured in North America.
 5 Year Warranty.



Performance

4000K - 120 Lm/W | 3500K - 116 Lm/W | 3000K - 112 Lm/W



Ordering Options

Sample Configuration: DTL U 120 - 2FT x 2FT - D 500 - I 500 - 90 - 4K - U - FR - FR - WH - AC - DIMOFF - N - 2 - N - 5 WIRE - CL - 6 - WH

Model	Size	Direct Lm/ft	Indirect Lm/ft	CRI	Color Temp	Voltage	Direct Lens
DTL U 120	4FT x 2FT	D 250	I 250	80	27K 2700K	U 120/277V	FR Frosted Flat
	6FT x 3FT	D 500	I 500	90	3K 3000K	H 347V	FRREG Frosted Regressed
		D 750	I 750		35K 3500K		
		D 1000	I 1000		4K 4000K		
		D _____ (custom up to 1200)	I _____ (custom up to 1200)		5K 5000K		
	-Custom Sizes Available - Please Consult Factory						

DTL U 120

Indirect Lens	Finish	Mounting	Driver	Controls
FR Frosted BATWING Batwing	WH White BLK Black GRY Grey CU Custom	AC Aircraft Cable 10' Standard	DIMOFF 0-10V DIMOFF <i>Optional</i> DALI LUTRON SR ELDO Lutron Ecosystem Philips SR .1% ELDO (347 only 1-10 5%)	N None <i>Optional</i> DMX SNS Philips SNS 300 w/BLD & Daylight CLM Encelium CLM LG LG Dongle BT Bluetooth Mesh EN Enlighted Integral
Indirect Lens: Minimum size 4FT x 2FT				

AC

Circuits	Accessories	Wiring	Wire Color	Wire Length	Canopy Color
1 1 Circuit 2 2 Circuits	N None <i>Optional</i> 10kV 10kV Surge Protection EM Emergency Battery +GTD Generator Transfer Device	5 WIRE 5 Wire(std) <i>Optional</i> N 5 Leads 6 WIRE 6 Wire - Cable (EM - emergency battery option)	CL Clear <i>Optional</i> B Black W White	Length(Ft) - 6Ft Standard	WH White BLK Black CU Custom - Consult factory for custom finishes

LED

L90>70,000

Samsung 301 2 McAdam Binning

4000K 120 Lm/W


3500K 98%

3000K 96%


90 CRI 85%

Lens Options - Direct Distribution


Lens Options - Indirect Distribution




Standard
Frosted Flat



Frosted
0.25" Regressed




Standard
Frosted




Batwing

Dimensions



Model	A	B
4FT x 2FT	22.8"	74.8"
6FT x 3FT	33.2"	110.8"

Mounting



Model	A	B
4FT x 2FT	22.5"	48.5"
6FT x 3FT	34.5"	72.5"

Finish Options

Standard Finishes



Grey
RAL 7046
Sandtex



White
RAL 9003
Sandtex



Black
RAL 9004
Sandtex

Custom Finishes



Orange
RAL 2009
Sandtex



Green
RAL 6010
Sandtex



Blue
RAL 5012
Sandtex



Yellow
RAL 1037
Sandtex

Additional finishes - Please contact factory