

Fixture: _____ QTY: _____ Project : _____


Thinline Octagon Suspended

Direct | Direct-Indirect

Architectural luminaire. Octagonal shaped design. Pendant mounting.
Direct and Direct-Indirect distribution options. 3 standards sizes.
Additional sizes available. 2.25" wide. Multiple finishes.

cULus Listed

Designed and manufactured in North America.
5 Year Warranty.



Performance

4000K - 120 Lm/W | 3500K - 116 Lm/W | 3000K - 112 Lm/W



Ordering Options

Sample Configuration: DTL OCTA - 8 x 2FT - D 500 - I 500 - 90 - 4K - U - FR - FR - WH - AC - DIMOFF - N - 2 - N - 5 WIRE - CL - 6 - WH

Model	Size	Direct Lm/ft	Indirect Lm/ft	CRI	Color Temp	Voltage	Direct Lens
DTL OCTA	8 x 2FT	D 250	I 250	80	27K 2700K	U 120/277V	FR Frosted Flat
	8 x 3FT	D 500	I 500	90	3K 3000K	H 347V	FRREG Frosted Regressed
	8 x 4FT	D 750	I 750		35K 3500K		
		D 1000	I 1000		4K 4000K		
	-Custom Sizes Available - Please Consult Factory	D _____ (custom up to 1200)	I _____ (custom up to 1200)		5K 5000K		

DTL OCTA

Indirect Lens	Finish	Mounting	Driver	Controls
FR Frosted BATWING Batwing	WH White BLK Black GRY Grey CU Custom	AC Aircraft Cable 10' Std	DIMOFF 0-10V DIMOFF <i>Optional</i> DALI LUTRON SR ELDO Lutron Ecosystem Philips SR .1% ELDO (347 only 1-10 5%)	N None <i>Optional</i> DMX SNS Philips SNS 300 w/BLD & Daylight CLM Encelium CLM LG LG Dongle BT Bluetooth Mesh EN Enlighted Integral

Indirect Lens: Minimum size 8FT x 2FT

- Contact factory for custom finishes

AC

Circuits	Accessories	Wiring	Wire Color	Wire Length	Canopy Color
1 1 Circuit 2 2 Circuits	N None <i>Optional</i> 10kV 10kV Surge Protection EM Emergency Battery +GTD Generator Transfer Device	5 WIRE 5 Wire (std) <i>Optional</i> N 5 Leads 6 WIRE 6 Wire - Cable (EM - emergency battery option)	CL Clear <i>Optional</i> B Black W White	Length(Ft) - 6Ft Standard	WH White BLK Black CU Custom <i>- Consult factory for custom finishes</i>

LED

L90>70,000

Samsung 301 2 McAdam Binning


4000K 120 Lm/W

3500K 98%


3000K 96%

90 CRI 85%

Lens Options - Direct Distribution




Standard
Frosted Flat




Frosted
0.25" Regressed

Lens Options - Indirect Distribution




Standard
Frosted



Batwing

Dimensions




Model	A	B
8 x 2FT	61.4"	61.4"
8 x 3FT	90.4"	90.4"
8 x 4FT	119.3"	119.3"

Note:

- 8 x 2FT - 1 Piece
- 8 x 3FT - 2 Pieces
- 8 x 4FT - 4 Pieces

Mounting



Model	A
8 x 2FT	24.5"
8 x 3FT	36.5"
8 x 4FT	48.5"

Finish Options

Standard Finishes



Grey
RAL 7046
Sandtex



White
RAL 9003
Sandtex



Black
RAL 9004
Sandtex

Custom Finishes



Orange
RAL 2009
Sandtex



Green
RAL 6010
Sandtex



Blue
RAL 5012
Sandtex



Yellow
RAL 1037
Sandtex

Additional finishes - Please contact factory