

Fixture: _____ QTY: _____ Project : _____

Lite Up

Linear Ambient High Bay

Contemporary style. Cutting edge design. Commercial and retail applications. Linear ambient direct-indirect high bay lighting.

White finish. 4' and 8' length options.

DLC Listed. cULus Listed.

Designed and manufactured in North America.

5 Year Warranty.



Ordering Options

Sample Configuration: ECOCTC4550 - 70 - 80 - 4K - U - WH - ND - AC - WFC12 - N - N

Model	Watts	CRI	Color Temp	Voltage	Finish	Orientation	Mounting
ECOCTC4550	60, 70	80	3K 3000K	U 120/277V	WH White	IND Indirect	AC Aircraft Cable
ECOCTC81100	80, 120, 160	90	35K 3500K 4K 4000K 5K 5000K	H 347V			

<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	WH	IND	AC
----------------------	----------------------	----------------------	----------------------	----------------------	-----------	------------	-----------

Wiring

WFC12 White Flexible Cord 12

Accessories

N None

Optional

DIMOFF 0-10V DIMOFF

EM Emergency Battery

Wifi

N None

Optional

Wifi Wifi

WFC12

<input type="text"/>	<input type="text"/>
----------------------	----------------------

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Features & Specifications

Efficacy:	Up to 143 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347V
Operating Temperature:	-20°C to +45°C -4°F to +113°F
Controls:	0-10V Dimming, WiFi
Mounting:	Aircraft Cable
Accessories:	0-10 1% Dim to off Driver, 90 Min 15W Emergency Battery

Output Performance

Model	Length	Watts	Lm/W	Delivered Lumens
ECOCTC4500 60	4	4000K	63.4	7,217
ECOCTC4500 70	4	4000K	70	10,000
ECOCTC811000 80	8	4000K	83	10,500
ECOCTC811000 120	8	4000K	126.7	14,434
ECOCTC811000 160	8	4000K	160	20,160

Dimensions

