

Fixture:

Project :

Del Wrap Surface Mount Wrap Around

LED wrap around fixture. Steel construction. Curved prismatic diffuser. Low maintenance and easy installation. Minimal lamp image.

QTY:

cULus Listed

Designed and manufactured in North America 5 Year Warranty





Ordering Options

Sample Configuration: DEL WRAP - 30 - 90 - 4K - U - PR - WH - 10 - N

| Model | Watts | CRI | Color Temp | Voltage | Lens | Finish | Width |
|-------------|----------------------|----------|--|----------------------|--------------------------|----------|--------------|
| DEL WRAP | 20 30 40 60 | 80 90 | 3K 3000K 35K 3500K 4K 4000K 5K 5000K | U 120/277V H 347V | PR Prismatic Lens | WH White | 10 10" Width |
| DEL WRAP | | | | | PR | WH | 10 |
| Accessories | | | | | | | |
| N None | | | | | | | |
| Optional | | | | | | | |

OCC Occupancy Sensor 10kV 10kV Surge Protection

Note: For custom configurations please contact factory

delviro energy

© delviro energy All Rights Reserved 1.877.502.3434 | info@delviro.com | www.delviro.com




Features & Specifications


| o to 153 Lm/W | | | |
|---|--|--|--|
| 90 | | | |
| 3000K, 3500K, 4000K, 5000K | | | |
| 100,000+ Life Hours (L70) | | | |
| 20/277V 347V | | | |
| 0°C to +40°C -40°F to +104°F | | | |
| 10V Dimming | | | |
| urface Mounting | | | |
| ccupancy Sensor (on/off), 10kV Surge Protection | | | |
| | | | |

Output Performance

| Model | Watts | Lm/W | Delivered Lumens |
|----------|-------|-------|------------------|
| Del Wrap | 20 | 152.6 | 3,052 |
| | 30 | 151.7 | 4,551 |
| | 40 | 150.7 | 6,028 |
| | 60 | 148.8 | 8,928 |

Dimensions





47.826″

delviro energy

© delviro energy All Rights Reserved 1.877.502.3434 | info@delviro.com | www.delviro.com