

Fixture: _____ QTY: _____ Project : _____

Titan HB 80

High Bay with Recessed Kit



Titan recessed fixture. Aluminum construction with polycarbonate protective lens. The perfect LED solution for industrial, commercial, warehouses, and large box retail applications.

DLC Listed. cULus Listed

Designed and manufactured in North America
5 Year Warranty



Ordering Options

Sample Configuration: TITANHB - 80 - 90 - 4K - U - FR - WH - TG - BFC - N

Model	Watts	CRI	Color Temp	Voltage	Lens	Finish	Mounting
TITAN HB	80	80	3K 3000K	U 120/277V	FR Frosted	WH White	TG T-Grid
		90	35K 3500K	H 347/480V	CL Clear	CU Custom	
			4K 4000K				
			5K 5000K				
TITAN HB	80	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	TG

Wiring

BFC Black Flexible Cord
WFC White Flexible Cord
IN Internal

Accessories

N None
Optional
OCC Occupancy Sensor (on/off)
WC Wireless Controls (consult factory)
BLD Bi-Level Dimming (100%/10%)
GCC Gasketed and Conformal Coated
DA Dimming Wire Accessible
10kV 10kV Surge Protection

Note: For custom configurations please contact factory. TitanHB Natatorium includes conformal coated boards and gasketing for damp and chlorine environments.

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Features & Specifications

Efficacy:	117.9 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347/480V
Operating Temperature:	-40°C to +40°C -40°F to +104°F
Controls:	0-10V Dimming
Mounting:	T-Grid
Accessories:	Occupancy Sensor (on/off), Wireless Controls, Bi-Level Dimming (100%/10%), 10kV Surge Protection, Dimming Wire, Emergency Battery, Gasketed and Conformal Coated

Output Performance

Model	Watts	Lm/W	Delivered Lumens
TitanHB 80	75.8	114	11,057

Dimensions

