

Fixture: \_\_\_\_\_ QTY: \_\_\_\_\_ Project : \_\_\_\_\_

# Troffer 2x2

## Retrofit Kit

2x2 LED troffer retrofit. 18 gauge aluminum. Easy installation with little maintenance. High gloss white finish. Offices, conference rooms, corridors, classrooms, hallways, cafeterias, retail, and general floor lighting applications.

DLC Listed

cETLus Listed

Designed and manufactured in North America

5 Year Warranty



### Ordering Options

**Sample Configuration:** TRFT2 2x2 - 15 - 80 - 4K - U - WH - RT

Model	Watts	CRI	Color Temp	Voltage	Finish	Mounting
TRFT2 2x2	15	80	3K 3000K	U 120/277V	WH White	RT Retrofit
	20	90	35K 3500K	H 347V		
	30		4K 4000K			
	40		5K 5000K			
	60					

TRFT2 2x2      **WH** **RT**

Note: For custom configurations please contact factory

### Features & Specifications

Efficacy:	Up to 114 Lm/W
CRI:	80   90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	150,000+ Life Hours (L70)
Voltage:	120/277V   347V
Operating Temperature:	-40°C to +40°C   -40°F to +104°F
Controls:	0-10V Dimming

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at [www.designlights.org/qpl](http://www.designlights.org/qpl).

### Output Performance

Model	Watts	Lm/W	Delivered Lumens
TRFT2 2x2 15	13.9	100.5	1,399
TRFT2 2x2 20	21.5	96.6	2,082
TRFT2 2x2 30	31.4	109.1	3,430
TRFT2 2x2 40	36.5	114.2	4,175
TRFT2 2x2 60	58.9	112.9	6,655

### Dimensions

