

Fixture: _____ QTY: _____ Project : _____

Troffer 2x4

Retrofit Kit

2x4 LED troffer retrofit. 18 gauge aluminum. Easy installation with little maintenance. High gloss white finish. Offices, conference rooms, corridors, classrooms, hallways, cafeterias, retail, and general floor lighting applications

DLC Listed

cETLus Listed

Designed and manufactured in North America

5 Year Warranty



Ordering Options

Sample Configuration: TRFT2 2x4 - 60 - 80 - 4K - U - WH - RT

Model	Watts	CRI	Color Temp	Voltage	Finish	Mounting
TRFT2 2x4	30	80	3K 3000K	U 120/277V	WH White	RT Retrofit
	40	90	35K 3500K	H 347V		
	60		4K 4000K			
	80		5K 5000K			
	120					

TRFT2 2x4 **WH** **RT**

Note: For custom configurations please contact factory

Features & Specifications

Efficacy:	Up to 117 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	150,000+ Life Hours (L70)
Voltage:	120/277V 347V
Operating Temperature:	-40°C to +40°C -40°F to +104°F
Controls:	0-10V Dimming

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Output Performance

Model	Watts	Lm/W	Delivered Lumens
TRFT2 2x4 30	27.9	117.1	3,270
TRFT2 2x4 40	38.2	116.4	4,446
TRFT2 2x2 60	57.6	110.3	6,361
TRFT2 2x2 80	77.9	106.2	8,276
TRFT2 2x2 120	120	110	13,200

Dimensions

