

Fixture: _____ QTY: _____ Project : _____

Zip Cloud

Surface

Contemporary and modern design. Powder coated aluminum extrusion. Seamless body. Surface mounting applications. 200,000 hr+ L70 w/Samsung LEDs.

cULus Listed

Designed and manufactured in North America
5 Year Warranty



Ordering Options

Sample Configuration: ZIP CLOUD - 44 - 120 - 90 - 4K - U - DIRECT - WH - SU - BFC 3 WIRE - DIMOFF

Model	Size	Watts	CRI	Color Temp	Voltage	Distribution	Finish
ZIP CLOUD	18	20, 40, 60, 70	80	3K 3000K	U 120/277V	DIRECT	WH White
	24	20, 40, 60, 80	90	35K 3500K	H 347V		BLK Black
	36	40, 80, 120, 160		4K 4000K			GRY Grey
	44	80, 120, 160		5K 5000K			CU Custom

- Consult factory for custom finishes

ZIP CLOUD DIRECT

Mounting	Wiring	Driver
SU Surface	IN Internal	DIMOFF 0-10V DIMOFF

Optional

- BFC 3 WIRE** Black 3 Conductor Wire _____
- BFC 5 WIRE** Black 5 Conductor Wire _____
- WFC 3 WIRE** White 3 Conductor Wire _____
- WFC 5 WIRE** White 5 Conductor Wire _____

SU DIMOFF _____

Features & Specifications

Efficacy:	120 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347V
Driver:	0-10 1% Dim to off driver
Mounting:	Surface

Output Performance

Model	Watts	Lm/W	Delivered Lumens
Zip Cloud 18	20	120	2,400
	40		4,800
	70		7,200
Zip Cloud 24	20	120	2,400
	40		4,800
Zip Cloud 36	40	120	4,800
	80		9,600
	120		14,400
	160		19,200
Zip Cloud 44	80	120	9,600
	120		14,400
	160		19,200

Dimensions

