

Fixture: _____ QTY: _____ Project : _____

Zip Flat

Suspended | Surface



LED Luminaire. 4' and 8' length options. 3' option available (consult factory). Steel construction. Frosted flat acrylic lens. Wall mountable option. Continuous run option. Enclosed lens prevents penetration of dust, insects, and other debris into the lamp compartment. Dry and Damp rated.

DLC Listed
cULus Listed

Designed and manufactured in North America
5 Year Warranty



Ordering Options

Sample Configuration: ZIP - 8 - 60 - 80 - 4K - U - FR - WH - V - BFC - N - FLAT

Model	Watts	CRI	Color Temp	Voltage	Lens	Finish
ZIP 4	20, 30, 40, 60	80	3K 3000K	U 120/277V	FRFL Frosted Flat	WH White
ZIP 8	40, 60, 80, 100, 120	90	35K 3500K	H 347V		
CU 96"			4K 4000K 5K 5000K			Optional CUBLK Custom Black
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	FRFL	<input type="text"/>

Mounting	Wiring	Accessories	Type
V V Hooks	BFC Black Flexible Cord	N None	FLAT
SU Surface	WFC White Flexible Cord	<i>Optional</i>	
<i>Optional</i>	IN Internal	OCC Occupancy Sensor (on/off)	
CR Continuous Run		EM Emergency Battery	
		10kV 10kV Surge Protection	
		MICRO Microwave Sensor - External (with BLD and Daylight Harvesting options)	
<input type="text"/>	<input type="text"/>	<input type="text"/>	FLAT

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.


Features & Specifications

Efficacy:	Zip 4: Up to 155 Lm/W Zip 8: Up to 158 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347V
Operating Temperature:	-35°C to +45°C -31°F to +113°F
Controls:	0-10V Dimming
Mounting:	V Hook, Surface Mount
Accessories:	Occupancy Sensor(on/off), Microwave Sensor, Emergency Battery, 10kV Surge Protection


Output Performance at 4K

Model	Watts	Lm/W	Delivered Lumens	Model	Watts	Lm/W	Delivered Lumens
Zip 4 20	18.90	150.26	2,840	Zip 8 40	39.26	157.62	6,188
Zip 4 30	29.08	153.30	4,458	Zip 8 60	59.24	155.09	9,172
Zip 4 40	39.26	154.74	6,075	Zip 8 80	79.26	154.67	12,259
Zip 4 60	59.14	152.96	9,046	Zip 8 100	99.38	154.42	15,346
				Zip 8 120	119.26	154.42	18,416

Dimensions



Photometrics



Zip 4 100 3K
Frosted Lens

ZONAL LUMEN SUMMARY

Zone	Lumens	% of Fixture
0° - 30°	3781	26%
0° - 60°	10647	73%
0° - 90°	14099	96%
90° - 120°	523	4%
90° - 150°	565	4%
90° - 180°	565	4%
0° - 180°	14665	100%
20° - 50°	6713	46%

ZONAL LUMEN SUMMARY

Zone	Lumens
0° - 10°	471
10° - 20°	1325
20° - 30°	1986
30° - 40°	2344
40° - 50°	2384
50° - 60°	2138
60° - 70°	1682
70° - 80°	1132
80° - 90°	638
90° - 100°	313
100° - 110°	147
110° - 120°	63
120° - 130°	26
130° - 140°	11
140° - 150°	4
150° - 160°	1
160° - 170°	0
170° - 180°	0