

Project :

# Zip Round

Suspended | Surface

Commercial LED luminaire. 2' and 4' length options. White finish with high impact acrylic lens. Pendant mounting with surface mount option. Enclosed lens prevents penetration of dust, insects, and other debris into the lamp compartment. DLC Listed cULus Listed

QTY:

Designed and manufactured in North America 5 Year Warranty





### **Ordering Options**

CRI Model Length Watts Color Temp Voltage Finish Lens **ZIP ROUND** 2 20, 30 80 ЗK 3000K **U** 120/277V FR Frosted WH White 20, 30, 40, 60, 80, 100 90 3500K **H** 347V 4 35K Optional **4K** 4000K 5000K 5K CL Clear **ZIP ROUND** WН Mounting Wiring Accessories V V Hooks BFC Black Flexible Cord N None WFC White Flexible Cord Optional Optional IN Internal SM Surface Mount occ Occupancy Sensor(on/off) UOCC Ultrasonic BLD Sensor BLD Bi Level Dimming(100%/10%) - Programmable EMBAT **Emergency Battery** 10kV 10kV Surge Protection Integral Programmable Microwave Sensor MICRO (with BLD and Daylight Harvesting options)

Sample Configuration: ZIP ROUND - 8 - 60 - 80 - 4K - U - FR - WH - V - BFC - N

Note: For custom configurations please contact factory

#### delviro energy

© delviro energy All Rights Reserved 1.877.502.3434 | info@delviro.com | www.delviro.com

### **Features & Specifications**

Efficacy:	Zip 2: Up to 142 Lm/W   Zip 4: Up to 155 Lm/W
CRI:	80   90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V   347V
Operating Temperature:	-35°C to +45°C   -31°F to +113°F
Controls:	0-10V Dimming
Mounting:	V Hook, Surface Mount
Accessories:	Occupancy Sensor(on/off), Ultrasonic BLD Sensor, Bi-Level Dimming (100%/1%), Microwave Sensor, Emergency Battery, 10kV Surge Protection

## **Output Performance at 4K**

Model	Watts	Lm/W	Delivered Lumens	Model	Watts	Lm/W	Delivered Lumens
Zip 2 20	20.63	141.88	2,927	Zip 4 20	18.90	150.26	2,840
Zip 2 30	30.95	141.87	4,391	Zip 4 30	29.08	153.30	4,458
				Zip 4 40	39.26	154.74	6,075
				Zip 4 60	59.14	152.96	9,046
				Zip 4 80	79.26	153.28	12,149
				Zip 4 100	99.20	153.74	15,251

#### **Dimensions**



6.05″

2': 24" | 4': 48"

#### delviro energy

© delviro energy All Rights Reserved 1.877.502.3434 | info@delviro.com | www.delviro.com