

Fixture: _____ QTY: _____ Project : _____

Zip Square

Suspended | Surface



LED linear. 2', 4, and 8' length options. Square profile.
Wall mountable option. Polycarbonate and acrylic lens options.
Enclosed lens prevents penetration of dust, insects, and other debris into the lamp compartment. Dry and damp rated.

DLC Listed
cULus Listed

Designed and manufactured in North America
5 Year Warranty



Ordering Options

Sample Configuration: ZIP - 8 - 60 - 80 - 4K - U - FR - WH - V - BFC - N - SQ

Model	Length	Watts	CRI	Color Temp	Voltage	Lens	Finish
ZIP	2	20, 30	80	3K 3000K	U 120/277V	FR Frosted	WH White
	4	20, 30, 40, 60, 80, 100	90	35K 3500K	H 347/480V	Optional CL Clear PC Polycarbonate	
	8	40, 60, 80, 100, 120		4K 4000K			
				5K 5000K			

ZIP WH

Mounting	Wiring	Accessories	Type
V V Hooks SU Surface <i>Optional</i> CR Continuous Run	BFC Black Flexible Cord WFC White Flexible Cord IN Internal	N None <i>Optional</i> OCC Occupancy Sensor (on/off) UOCC Ultrasonic BLD Sensor EM Emergency Battery 10kV 10kV Surge Protection MICRO Integral Programmable Microwave Sensor (with BLD and Daylight Harvesting options)	SQ Square

SQ

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Features & Specifications

Efficacy:	Zip 2: Up to 142 Lm/W Zip 4: Up to 155 Lm/W Zip 8: Up to 158 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347V
Operating Temperature:	-35°C to +45°C -31°F to +113°F
Controls:	0-10V Dimming
Mounting:	V Hook, Surface Mount
Accessories:	Occupancy Sensor(on/off), Ultrasonic BLD Sensor, Integral Programmable Microwave Sensor, Emergency Battery, 10kV Surge Protection

Output Performance

Model	Watts	Lm/W	Delivered Lumens
Zip 2 20	20.63	141.88	2,927
Zip 2 30	30.95	141.87	4,391

Model	Watts	Lm/W	Delivered Lumens
Zip 4 20	18.90	150.26	2,840
Zip 4 30	29.08	153.30	4,458
Zip 4 40	39.26	154.74	6,075
Zip 4 60	59.14	152.96	9,046
Zip 4 80	79.26	153.28	12,149
Zip 4 100	99.20	153.74	15,251

Note: Zip 4 100 - 120/277V Only

Model	Watts	Lm/W	Delivered Lumens
Zip 8 40	39.26	157.62	6,188
Zip 8 60	59.24	155.09	9,172
Zip 8 80	79.26	154.67	12,259
Zip 8 100	99.38	154.42	15,346
Zip 8 120	119.26	154.42	18,416

Note: Zip 8 100 - 120/277V Only

Dimensions

