

Fixture: _____ QTY: _____ Project : _____

Zoom High Bay

Energy efficient LED luminaire. Aluminum construction. Pendant mounting. Architectural, retail, industrial, and commercial high bay applications. White finish. Custom finishes available. Aluminum and acrylic reflector options.

DLC Listed
cULus Listed

Designed and manufactured in North America
5 Year Warranty



Ordering Options

Sample Configuration: ZOOM - 90 - 90 - 4K - U - 16AC - WH - H - BFC - N - NL

| Model | Watts | CRI | Color Temp | Voltage | Dome Type | Finish | Mounting |
|-------|----------------------|----------------------|----------------------|----------------------|-----------------------|---------------------------------------|----------|
| ZOOM | 50 | 80 | 3K 3000K | U 120/277V | 16AC 16 Clear Acrylic | WH White | H Hook |
| | 70 | 90 | 35K 3500K | H 347V | 16AL 16 Aluminum | CU Custom | |
| | 90 | | 4K 4000K | | | | |
| | 120 | | 5K 5000K | | | | |
| | 150 | | | | | | |
| | 180 195 | | | | | | |
| | | | | | | - Consult factory for custom finishes | |
| ZOOM | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/> | H |

| Wiring | Accessories | Lens |
|--------------------------------|-----------------------------------|---------------------------|
| BFC Black Flexible Cord | N None | NL No Lens |
| WFC White Flexible Cord | <i>Optional</i> | CLD Clear Diffused |
| | DA Dimming Wire Accessible | |
| | 10kV 10kV Surge Protection | |
| | DIMOFF 0-10% DIMOFF | |
| <input type="text"/> | <input type="text"/> | <input type="text"/> |

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Features & Specifications

| | |
|-------------------------------|---|
| Efficacy: | Up to 138 Lm/W |
| CRI: | 80 90 |
| Color Temperature: | 3000K, 3500K, 4000K, 5000K |
| Lumen Maintenance: | 200,000+ Life Hours (L70) |
| Voltage: | 120/277V 347/480V |
| Operating Temperature: | -40°C to +50°C -40°F to +122°F |
| Controls: | 0-10V Dimming |
| Mounting: | Hook |
| Accessories: | Dimming Wire Accessible, 10kV Surge Protection, 0-10V Dim to off Driver |

Output Performance

| Model | Watts | Lm/W | Delivered Lumens |
|----------|-------|-------|------------------|
| Zoom 50 | 50 | 125 | 6,250 |
| Zoom 70 | 75.6 | 138.1 | 10,709 |
| Zoom 90 | 87.4 | 132.9 | 11,617 |
| Zoom 120 | 120.1 | 114.7 | 15, 405 |
| Zoom 150 | 152.3 | 122.9 | 18,722 |
| Zoom 180 | 178.7 | 121 | 21,632 |
| Zoom 195 | 199.8 | 119.7 | 23,911 |

Dimensions

