

Fixture: _____ QTY: _____ Project : _____

Lite Up

Linear Ambient High Bay

Contemporary style. Cutting edge design. Commercial and retail applications. Linear ambient direct-indirect high bay lighting. White finish. 4' and 8' length options. Dry and damp rated.

DLC Premium. cULus Listed

Designed and manufactured in North America
5 Year Warranty



Ordering Options

Sample Configuration: ECOCTC4550 - 70 - 80 - 4K - U - WH - ND - AC - WFC12 - N - N

Model	Watts	CRI	Color Temp	Voltage	Finish	Orientation	Mounting
ECOCTC4550	60, 70	80	3K 3000K	U 120/277V	WH White	IND Indirect	AC Aircraft Cable
ECOCTC81100	80, 120, 160	90	35K 3500K 4K 4000K 5K 5000K	H 347V			

<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	WH	IND	AC
----------------------	----------------------	----------------------	----------------------	----------------------	-----------	------------	-----------

Wiring	Accessories	Controls
WFC12 White Flexible Cord 12	N None	N None
	<i>Optional</i>	<i>Optional</i>
	DIMOFF 0-10V DIMOFF	SIL Silvair
	EM Emergency Battery	

WFC12	<input type="text"/>	<input type="text"/>
--------------	----------------------	----------------------

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Features & Specifications

Efficacy:	4': Up to 150 Lm/W 8': Up to 151 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347V
Operating Temperature:	-20°C to +45°C -4°F to +113°F
Controls:	Silvair
Mounting:	Aircraft Cable
Accessories:	0-10 1% Dim to off Driver, 90 Min 15W Emergency Battery

Output Performance

Model	Length	CCT	Watts	Lm/W	Delivered Lumens
ECOCTC4500 60	4	4000K	62.44	150.05	9,369
ECOCTC4500 70	4	4000K	70	142.85	10,000
ECOCTC811000 80	8	4000K	83	126.51	10,500
ECOCTC811000 120	8	4000K	124.17	151.46	18,807
ECOCTC811000 160	8	4000K	156.81	147.00	23,051

Dimensions

