

Fixture: _____ QTY: _____ Project : _____

Zoom High Bay

Energy efficient LED luminaire. Aluminum construction. Pendant mounting. Architectural, retail, industrial, and commercial high bay applications. White finish. Custom finishes available.

Aluminum and acrylic reflector options.

DLC Listed
cULus Listed

Designed and manufactured in North America
5 Year Warranty



Ordering Options

Sample Configuration: ZOOM - 90 - 90 - 4K - U - 16AC - WH - H - BFC - N - NL

Model	Watts	CRI	Color Temp	Voltage	Dome Type	Finish	Mounting
ZOOM	50	80	3K 3000K	U 120/277V	16AC 16 Clear Acrylic	WH White	H Hook
	70	90	35K 3500K	H 347V	16AL 16 Aluminum	CU Custom	
	90		4K 4000K			- Consult factory for custom finishes	
	120		5K 5000K				
	150						
180							
195							

ZOOM H

Wiring	Accessories	Lens
BFC Black Flexible Cord	N None	NL No Lens
WFC White Flexible Cord	Optional	CLD Clear Diffused
	DA Dimming Wire Accessible	
	10kV 10kV Surge Protection	

Note: For custom configurations please contact factory

Note: Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.

Features & Specifications

Efficacy:	Up to 138 Lm/W
CRI:	80 90
Color Temperature:	3000K, 3500K, 4000K, 5000K
Lumen Maintenance:	200,000+ Life Hours (L70)
Voltage:	120/277V 347/480V
Operating Temperature:	-40°C to +50°C -40°F to +122°F
Controls:	0-10V Dimming
Mounting:	Hook
Accessories:	Dimming Wire Accessible, 10kV Surge Protection

Output Performance

Model	Watts	Lm/W	Delivered Lumens
Zoom 50	50	125	6,250
Zoom 70	75.6	138.1	10,709
Zoom 90	87.4	132.9	11,617
Zoom 120	120.1	114.7	15,405
Zoom 150	152.3	122.9	18,722
Zoom 180	178.7	121	21,632
Zoom 195	199.8	119.7	23,911

Dimensions

