

Fixture: _____ QTY: _____

Project: _____


Thinline Curve Acoustic

Suspended Direct, Direct/Indirect, Indirect

Our pendant mounted acoustic light fixture combines the best of lighting and sound absorption technology.

Our innovative lighting solution not only illuminates your environment with brilliant LED light but also enhances the acoustics of the room, creating an environment that is both visually stunning and acoustically pleasing.

Designed and Manufactured in North America.



Specifications

LED	Samsung 301 3-Step MacAdam Binning L90>70,000 4000K - 120 Lm/W 3500K - 96% 3000K - 90%	Driver	0-10 DIMOFF Optional: DALI, Lutron, Philips SR, ELDO
CRI	80, 90	Control Options	DMX, Philips SNS 300, Encelium CLM, LG Dongle, Bluetooth Mesh, Enlighted Integral
Direct Watts/Ft	2.5W, 3.5W, 5W, 7.5W, 10W	Accessories	10kV Surge Protection, Emergency Battery, Generator Transfer Device
Indirect Watts/Ft	2.5W, 3.5W, 5W, 7.5W, 10W	Wiring	5 Leads Optional: 5 Wire, 6 Wire (cable, emergency battery option)
Color Temp	2700K, 3000K, 3500K, 4000K, 5000K	Felt	100% Post-consumer recycled polyester Thickness: 3.175mm 0.125" 500 gsm (14.75 opsy) E84 compliant 33 Vibrant colors
Voltage	120/277, 347V	Certifications	cULus Dry and Damp Rated
Construction	Aluminum extruded with cast end caps	Warranty	5-Year Warranty
Dimensions	Widths: 3.18" Height: 4.125" Length: 4' Radius: 5' Curve: 45°		
Mounting	Aircraft Cable 10" Standard Optional: T-Bar 9/16 Clip, T-Bar 15/16 Clip		
Connection	C-Type, S-Type		
Lens Direct	Frosted Flat Optional: Frosted Regressed, Asymmetric 0.5" Drop Lens, 1" Drop Lens, Louver		
Lens Indirect	Frosted Flat Optional: Asymmetric, Batwing		

Output Performance - Direct

Model	Watts/Ft	Lm/W	Delivered Lumens/Per Foot	Delivered Lumens/Per Section
DTL 4	2.5	100	250	1,000
	3.5	100	350	1,400
	5	100	500	2,000
	7.5	100	750	3,000
	10	100	1000	5,000


- Watts per foot available on all lengths
- LPW is with Frosted Lens

Output Performance - Indirect


Model	Watts/Ft	Lm/W	Delivered Lumens/Per Foot	Delivered Lumens/Per Section
DTL 4	2.5	100	250	1,000
	3.5	100	350	1,400
	5	100	500	2,000
	7.5	100	750	3,000
	10	100	1000	5,000

- Watts per foot available on all lengths
- LPW is with Frosted Lens

Lens Options - Direct Distribution




Lens Options - Indirect Distribution




Standard
Frosted

Dimensions




Note: End Cap Thickness=0.1". Add additional two End Cap thickness of 0.2" to length

Mounting




Aircraft Cable

Connection Type




C - Connect




S - Connect


Sample Configurations




8x4' Section
Circle



4x4' Section
1/2 Circle



2x4' Section
1/4 Circle




4' Section
Linear Shapes

Eco Lux Designer Felt Color Options



Ordering Options

Sample Configuration: DTL A CRV - C - 3 - 80 - 5 - 5 - 4K - U - FR - FR - Light Grey - AC - DIMOFF - N - 2 - N - 5 Wire - CL - 6 - WH



Model	Connection	Continuous Run	CRI	Direct Watts/ft	Indirect Watts/Ft	Color Temp	Voltage
DTL A CRV	C S	CR _____	80	2.5	2.5	27K - 2700K	U - 120/277V
		<i>Please specify number of sections</i>	90	3.5	3.5	3K - 3000K	H - 347V
				5	5	35K - 3500K	
				7.5	7.5	4K - 4000K	
				10	10	5K - 5000K	

Direct Lens	Indirect Lens	Felt Color	Mounting	Driver	Controls
FR - Frosted	FR - Frosted	Color ____ <i>- Please see color options</i>	AC - Aircraft Cable 10' Standard	DIMOFF - 0-10 DIMOFF <i>Optional</i> DALI - Digital Addressable Lighting Interface LUTRON - Lutron Ecosystem SR - Philips SR ELDO - 1% ELDO (347 only 1-10 5%)	N - None <i>Optional</i> DMX - Digital Multiplex SNS - Philips SNS 300 w/BLD & Daylight CLM - Encelium CLM LG - LG Dongle BT - Bluetooth Mesh EN - Enlighted Integral

Circuits	Accessories	Wiring	Wire Color	Wire Length	Canopy Color
1 - 1 Circuit 2 - 2 Circuit	N - None <i>Optional</i> 10kV - 10kV Surge Protection EM - Emergency Battery +GTD - Generator Transfer Device Note: - For Emergency Battery (EM), minimum length is 4' (direct distribution), 8' (indirect distribution)	5 Wire - 5 Wire Standard <i>Optional</i> N - 5 Leads 6 WIRE - 6 Wire	CL - Clear <i>Optional</i> B - Black W - White	Length(ft)____ 6' Standard	WH - White RAL 9003 BLK - Black RAL 9004 CU - Custom <i>- Please contact factory for custom finishes</i>