

Date	Fixture	Project	Quantity
------	---------	---------	----------

# VTs

## Vapor Tight

### Features

- Weatherproof LED fixture
- Enclosed and gasketed body protects electronics from harsh weather elements
- 4' and 8' lengths
- Polycarbonate shatterproof housing
- Moisture, vapor, chemical resistant, corrosion free, and dust protective
- NSF available
- Designed and Manufactured in North America
- 5 Year Warranty



### Specifications

#### Construction

Polycarbonate, Shatterproof Housing  
 Stainless Steel Latches  
 IP 65 (Grey Body - Standard)  
 IP 67 (White Body - Custom Order)

#### Dimensions

VTs 4: 6"W x 50"L x 4.25"H  
 VTs 8: 6"W x 102"L x 4.25"H

#### LED

Samsung LM281B Plus Pro, 3-Step MacAdam Binning  
 200,000+ Life Hours (L70)

#### Efficacy

VTs 4: Up to 155 Lm/W  
 VTs 8: Up to 152 Lm/W

#### Watts

VT4s: 30W, 40W, 60W, 80W  
 VT8s: 40W, 60W, 80W, 120W

#### Color Temperature

3000K - 5000K

#### CRI

80 or 90

#### Voltage

120/277V or 347/480V

#### Controls

0-10V Dimming down to 1%

#### Operating Temperature

-40°C to +40°C | -40°F to +104°F  
 +55°C | +131°F - option

#### Lens

Frosted or Clear

#### Mounting

Aircraft Cable  
 V-Clips

#### Accessories

Occupancy Sensor (on/off)  
 Waterproof Occupancy Sensor,  
 Bi-Level Dimming  
 Waterproof Bi-Level Dimming,  
 10kV Surge Protection  
 Emergency Battery

#### Wiring

Black or White Flexible Cord

#### Finishes

Grey  
 White - Custom

#### Certifications

DLC Premium  
 DLC  
 cULus

Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at [www.designights.org/qpl](http://www.designights.org/qpl).



## Ordering Guide

Sample Configuration: VT4s - 60 - 80 - 4K - U - FR - GRY - AC - BFC - N - IP65 - N

Model	Watts	CRI	Color Temp	Voltage	Lens	Finish	Mounting	Wiring	Accessories
Enclosure	NSF								

Model	Watts	CRI	Color Temp	Voltage	Lens	Finish	Mounting
<b>VT4s</b>	<b>30, 40, 60, 80</b>	<b>80</b>	<b>3K - 3000K</b>	<b>U - 120/277V</b>	<b>FR - Frosted</b>	<b>GRY - Grey</b>	<b>AC - Aircraft Cable</b>
<b>VT8s</b>	<b>40, 60, 80, 120</b>	<b>90</b>	<b>35K - 3500K</b> <b>4K - 4000K</b> <b>5K - 5000K</b>	<b>H - 347/480V</b>	<b>CL - Clear</b>	<i>Optional</i> <b>WH - White*</b>	<b>V - V Hooks</b>
						Note: Custom order, consult factory	

Wiring	Accessories	Enclosure	NSF
<b>BFC - Black Flexible Cord</b> <b>WFC - White Flexible Cord</b>	<b>N - None</b> <i>Optional</i> <b>OCC - Occupancy Sensor (on/off)</b> <b>BLD - Bi-Level Dimming (100%/10%)</b> <b>WBD - Waterproof Bi-Level Dimming (100%/10%)</b> <b>WOC - Waterproof Occupancy Sensor (on/off)</b> <b>10kV - 10kV Surge Protection</b> <b>EM - Emergency Battery</b>	<b>IP65 - Standard (Grey Body)</b> <b>IP67 - White Body (Custom Order)</b>	<b>N - None</b> <b>NSF - White Body*</b>  Note: Custom order, consult factory


Note: For custom configurations please contact factory

## Dimensions




W: 6.1"  
H: 4.25"

### VT4s



35.5"




50.0"

### VT8s



87.5"



102.0"

## Output Performance

Model	Watts	Lm/W	Delivered Lumens	Model	Watts	Lm/W	Delivered Lumens
VT4s 30	29.82	158.22	4718	VT8s 40	42.07	165.43	6960
VT4s 40	42.07	156.09	6567	VT8s 60*	64.84	164.87	10690
VT4s 60*	64.84	153.96	9983	VT8s 80*	78.25	164.30	12856
VT4s 80*	78.25	149.70	11715	VT8s 120*	117.38	163.17	19153

Note: \* DLC Premium