

Date	Fixture	Project	Quantity

# **Zip Cloud**

# **Recessed Drywall**

#### **Features**

- · Architectural luminaire
- · Sleek circular shape
- · Recessed lighting
- 4 size options
- · Designed and Manufactured in North America
- 5 Year Warranty



# **Specifications**

#### Construction

Aluminum extruded body
Dry and damp rated for indoor applications

# **Dimensions**

Diameter: 18", 24", 36", 44" Height: 4"

# **LED**

Samsung LM281B Plus Pro, 3-Step MacAdam Binning 120 Lm/W L70>200,000

# Watts

Zip Cloud 18: 20W, 40W, 60W, 70W Zip Cloud 24: 20W, 40W, 60W, 80W Zip Cloud 36; 40W, 80W, 120W, 160W Zip Cloud 44: 80W, 120W, 160W

#### **Color Temperature**

2700K - 5000K

### CRI

80 or 90

# Voltage

120/277V or 347V

#### Driver

0-10V Dimming down to 1% No Dimming

#### Lens

Frosted Flat

## Mounting

Recessed drywall

# Wiring

Black and White 3 Conductor Wire (No Dimming) Black and White 5 Conductor Wire

# **Finishes**

White - RAL 9003

#### Certifications

cULus







# **Ordering Guide**

Sample Configuration: ZIP CLOUD - 18 - 70 - 80 - 4K - U - FR - DIRECT - WH - REC - DIMOFF - IN

ZIP CLOUD REC						FR	DIRECT	WH	REC
Model	Size	Watts	CRI	Color Temp	Voltage	Lens	Distribution	Finish	Mounting
Driver	Wiring								


Model	Size	Watts	CRI	Color Temp	Voltage	Lens	Distribution
ZIP CLOU REC	18 24 36 44	18: 20, 40, 60, 70 24: 20, 40, 60, 80 36: 40, 80, 120, 160 44: 80, 120, 160	80 90	<b>3K</b> - 3000K <b>35K</b> - 3500K <b>4K</b> - 4000K <b>5K</b> - 5000K	<b>U</b> - 120/277V <b>H</b> - 347V	FR - Frosted Flat	DIRECT

Finish	Mounting	Driver	Wiring
WH - White	REC - Recessed	DIMOFF - 0-10V Dimming down to 1% ND - No Dimming	IN - Internal Optional BFC 3 Wire - Black 3 Conductor Wire (no dimming) WFC 3 Wire - White 3 Conductor Wire (no dimming BFC 5 Wire - Black 5 Conductor Wire WFC 5 Wire - White 5 Conductor Wire

For the latest product information please visit www.delviro.com



# **Dimensions**



Ø: 18", 24", 36", 44" Ø(w/ trim): 18.75", 25", 37.25", 45" H: 4.0"

# **Output Performance**

Model	Watts	Lm/W	Delivered Lumens
Zip Cloud 18	20 40 60 70	120	2,400 4,800 7,200 8,400
Zip Cloud 24	20 40 60 80	120	2,400 4,800 7,200 9,600
Zip Cloud 36	40 80 120 160	120	4,800 9,600 14,400 19,200
Zip Cloud 44	80 120 160	120	9,600 14,400 19,200

# Mounting

