

Date	Fixture	Project	Quantity
------	---------	---------	----------

Zoom High Bay

Features

- Energy efficient LED high bay
- Aluminum body
- Architectural, retail, industrial, and commercial high bay application
- Acrylic and aluminum reflector options
- Dry and damp rated
- Designed and Manufactured in North America
- 5 Year Warranty



Specifications

Construction

Aluminum Housing
Power Coated Finish

Dimensions

Ø 16.22" x 16" H

LED

Samsung LM281B Plus Pro, 3-Step MacAdam Binning
180,000+ Life Hours (L70)

Efficacy

Up to 141 Lm/W

Watts

50W - 195W

Color Temperature

3000K - 5000K

CRI

80 or 90

Voltage

120/277V or 347/480V

Controls

0-10V Dimming down to 1%

Operating Temperature

-40°C to +50°C
-40°F to +122°F

Dome Type

Clear Acrylic
Aluminum

Lens

No Lens
Clear Diffused

Mounting

Hook

Accessories

Dimming Wire
10kV Surge Protection

Wiring

Black or White Flexible Cord

Finishes

White - RAL 9003
Custom RAL finishes available

Certifications

DLC
cULus

Not all products are qualified on the DLC QPL. To view our DLC qualified products, please consult the DLC qualified products list at www.designlights.org/qpl.



Ordering Guide


Sample Configuration: ZOOM - 90 - 80 - 4K - U - 16AC - WH - H - BFC - N - NL

ZOOM							H		
Model	Watts	CRI	Color Temp	Voltage	Dome Type	Finish	Mounting	Wiring	Accessories
Lens									

Model	Watts	CRI	Color Temp	Voltage	Dome Type	Finish	Mounting
ZOOM	50	80	3K - 3000K	U - 120/277V	16AC - 16 Clear Acrylic 16AL - 16 Aluminum	WH - White CU - Custom* Note: Consult factory for custom finishes	H - Hook
	70		90	35K - 3500K			
	90		4K - 4000K				
	120		5K - 5000K				
	150						
	180						
	195						

Wiring	Accessories	Lens		
BFC - Black Flexible Cord WFC - White Flexible Cord	N - None <i>Optional</i> OCC - Occupancy Sensor (on/off) EM - Emergency Battery BLD - Bi-Level Dimming (100%/10%) 10kV - 10kV Surge Protection	NL - No Lens CLD - Clear Diffused		

Dimensions



Ø: 16.22"
H: 16"

Output Performance

Model	Watts	Lm/W	Delivered Lumens
Zoom 70	73.12	141	10310
Zoom 90	94	137.3	12906
Zoom 120	125.35	133.5	16746
Zoom 150	145.59	129.87	18908
Zoom 180	174.71	128	22363
Zoom 195	189.27	126.14	23875