

Date	Fixture	Project	Quantity
------	---------	---------	----------

Zip Round

Linear Strip Light

Features

- LED linear light fixture
- Pendant and surface mounting options
- 2', 4' and 8' lengths
- Enclosed lens prevents penetration of dust, insects, and other debris into the lamp compartment
- Dry and damp rated
- Designed and Manufactured in North America
- 5 Year Warranty



Specifications

Construction

Aluminum Housing
Powder Coated Finish

Dimensions:

Zip Round 2: 23.6"
Zip Round 4: 46.1"
Zip Round 8: 91.1"

LED

Samsung LM281B Plus Pro, 3-Step MacAdam Binning
200,000+ Life Hours (L70)

Watts

Zip Round 2: 20W, 30W
Zip Round 4: 20W - 100W
Zip Round 8: 40W - 120W

Color Temperature

3000K - 5000K

CRI

80 or 90

Voltage

120/277V or 347V

Controls

0-10V Dimming down to 1%

Operating Temperature

-35°C to +45°C | -31°F to +113°

Lens

Frosted
Clear

Mounting

Aircraft Cable (10' std)
V-Hooks
Surface

Accessories

Occupancy Sensor (*on/off*)
Ultrasonic Occupancy Sensor
Bi-Level Dimming - Programmable (100%/10%)
Emergency Battery
10kV Surge Protection
Microwave Sensor -External (with BLD and Daylight Harvesting options)

Wiring

Black or White Flexible Cord
Internal

Finishes

White - RAL 9003

Certifications

cULus



Ordering Guide

Sample Configuration: ZIP - 4 - 60 - 80 - 4K - U - FR - WH - AC - BFC - N - RND

ZIP							WH		
Model	Length	Watts	CRI	Color Temp	Voltage	Lens	Finish	Mounting	Wiring
	RND								
Accessories	Type								

Model	Length	Watts	CRI	Color Temp	Voltage	Lens	Finish
ZIP	2	20, 30	80	3K - 3000K	U - 120/277V	FR - Frosted	WH - White
	4	20, 30, 40, 60, 80, 100	90	35K - 3500K	H - 347V	Optional	
	8	40, 60, 80, 100, 120		4K - 4000K 5K - 5000K		CL - Clear	


Mounting	Wiring	Accessories	TYPE
AC - Aircraft Cable 6' std V - V Hooks SU - Surface <i>Optional</i> CR - Continuous Run	IN - Internal BFC - Black Flexible Cord WFC - White Flexible Cord	N - None <i>Optional</i> OCC - Occupancy Sensor (on/off) UOCC - Ultrasonic Occupancy Sensor BLD - Bi-Level Dimming - Programmable (100%/10%) EM - Emergency Battery 10kV - 10kV Surge Protection MICRO - Microwave Sensor -External (with BLD and Daylight Harvesting options)	RND

Note: For custom configurations please contact factory


Dimensions




W: 6.01"
H: 3.58"



2': 23.6"




4': 46.1"



8': 91.1"

Output Performance at 4K

Model	Watts	Lm/W	Delivered Lumens
Zip 4 20	18.9	131.3	2477
Zip 4 30	30	131.3	3939
Zip 4 40	37.7	131.3	4954
Zip 4 60	60.0	131.3	7878
Zip 4 80	75.5	131.3	9907
Zip 4 100	100.0	131.3	13130

Photometrics


Zip 4-80, 4K
Frosted Lens

ZONAL LUMEN SUMMARY

Zone	Lumens	% of Fixture
0° - 30°	2711	27%
0° - 60°	7550	76%
0° - 90°	9765	98%
90° - 120°	154	2%
90° - 150°	154	2%
90° - 180°	154	2%
0° - 180°	9919	100%
20° - 50°	4771	48%

ZONAL LUMEN SUMMARY

Zone	Lumens
0° - 10°	339
10° - 20°	951
20° - 30°	1421
30° - 40°	1668
40° - 50°	1682
50° - 60°	1488
60° - 70°	1141
70° - 80°	723
80° - 90°	352
90° - 100°	123
100° - 110°	28
110° - 120°	3
120° - 130°	0
130° - 140°	0
140° - 150°	0
150° - 160°	0
160° - 170°	0
170° - 180°	0